Baureihe 5 (E60) - Limousine

Stand 03/03

520i/iA (M54)						
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM (12=LM- Bandrad)	
Sommer:						
205/60 R 16 92V	7J x 16	7J x 16	20	12	12,50,115,134	
225/55 R 16 95V	7J x 16	7J x 16	20	12	12,50,115,134	
225/50 R 17 94W	-	7½J x 17	20	-	116,138	
245/45 R 17 95W 1)	-	8J x 17	20	-	122,144	
245/40 R 18 93W 1)	-	8J x 18	20	-	32,71,89,123,124	
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93W	-	8J x 18	20	-	32,89,124	
HA: 275/35 R 18 95W	-	9J x 18	32	-	32,89,124	
19"-Mischbereifung: 1)						
VA: 245/35 R 19 89Y	-	8J x 19	20	-	101,125,128	
HA: 275/30 R 19 92Y	-	9½J x 19	32	-	101,125,128	
Winter (M+S):						
205/60 R 16 92Q/T/H	7J x 16	7J x 16	20	12	12,50,115,134	
225/55 R 16 95Q/T/H	7J x 16	7J x 16	20	12	12,50,115,134	
225/50 R 17 94Q/T/H	-	7½J x 17	20	-	116,138	
245/45 R 17 95V 1)	-	8J x 17	20	-	122,144	
Reserverad:						
T 135/80 R 17 102M 1)	4.00B x 17	-	18	12		

Baureihe 5 (E60) - Limousine

Stand 03/03

530i/iA (M54), 530d/dA (M57)						
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM (12=LM- Bandrad)	
Sommer:						
225/55 R 16 95W	-	7J x 16	20	-	50,115,134	
225/50 R 17 94W	-	7½J x 17	20	-	116,138	
245/45 R 17 95W 1)	-	8J x 17	20	-	122,144	
245/40 R 18 93W 1)	-	8J x 18	20	-	32,71,89,123,124	
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93W	-	8J x 18	20	-	32,89,124	
HA: 275/35 R 18 95W	-	9J x 18	32	-	32,89,124	
19"-Mischbereifung: 1)						
VA: 245/35 R 19 89Y	-	8J x 19	20	-	101,125,128	
HA: 275/30 R 19 92Y	-	9½J x 19	32	-	101,125,128	
Winter (M+S):						
225/55 R 16 95Q/T/H	-	7J x 16	20	-	12,50,115,134	
225/50 R 17 94Q/T/H	-	7½J x 17	20	-	116,138	
245/45 R 17 95V 1)	-	8J x 17	20	-	122,144	
Reserverad:						
T 135/80 R 17 102M 1)	4.00B x 17	-	18	12		

Baureihe 5 (E60) - Limousine

520i/iA (M54)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.	
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
205/60 R 16 92V	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/55 R 16 95V	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144
245/40 R 18 93W 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2	20	-	32,89,124
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2	32	-	32,89,124
19"-Mischbereifung: 1)						
VA: 245/35 R 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128
VA: 245/35 R 19 93Y XL	RSC	-	8½J x 19 EH2	18	-	125,128
HA: 275/30 R 19 96Y XL	RSC	-	9½J x 19 EH2	32	-	125,128
Winter (M+S):						
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/50 R 17 94H	Std/RSC	_	7½J x 17 EH2	20	-	116,138
245/45 R 17 95V 1)	RSC	-	8J x 17 EH2	20	-	122,144
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E60) - Limousine

525i/iA (M54)	525i/iA (M54)						
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:							
225/55 R 16 95W	Std -	7J x 16 H2	20	-	50,115,134		
225/50 R 17 94W Std/R	SC -	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95W 1)	SC -	8J x 17 EH2	20	-	122,144		
245/40 R 18 93W 1)	SC -	8J x 18 EH2	20	-	32,71,89,123,124,129		
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W	SC -	8J x 18 EH2	20	-	32,89,124		
HA: 275/35 R 18 95W	SC -	9J x 18 EH2	32	-	32,89,124		
19"-Mischbereifung: 1)							
VA: 245/35 R 19 93Y XL	Std -	8J x 19 EH2	20	-	101,125,128		
HA: 275/30 R 19 96Y XL	Std -	9½J x 19 EH2	32	-	101,125,128		
VA: 245/35 R 19 93Y XL	SC -	8½J x 19 EH2	18	-	125,128		
HA: 275/30 R 19 96Y XL	SC -	9½J x 19 EH2	32	-	125,128		
Winter (M+S):							
225/55 R 16 95H	Std 7J x 16 H2	7J x 16 H2	20	12	50,115,134		
225/50 R 17 94H Std/F	SC -	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95V 1)	SC -	8J x 17 EH2	20	-	122,144		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E60) - Limousine

525d/dA (M57), 530d/dA (M	57), 530i/iA (M5	4)			
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.	
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/55 R 16 95W S	td -	7J x 16 H2	20	-	50,115,134
225/50 R 17 94W Std/RS	C -	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1) RS	С -	8J x 17 EH2	20	-	122,144
245/40 R 18 93W 1) RS	С -	8J x 18 EH2	20	-	32,71,89,123,124,129
18"-Mischbereifung: 1)					
VA: 245/40 R 18 93W RS	С -	8J x 18 EH2	20	-	32,89,124
HA: 275/35 R 18 95W RS	С -	9J x 18 EH2	32	-	32,89,124
19"-Mischbereifung: 1)					
VA: 245/35 R 19 93Y XL S	td -	8J x 19 EH2	20	-	101,125,128
HA: 275/30 R 19 96Y XL S	td -	9½J x 19 EH2	32	-	101,125,128
VA: 245/35 R 19 93Y XL RS	С -	8½J x 19 EH2	18	-	125,128
HA: 275/30 R 19 96Y XL RS	С -	9½J x 19 EH2	32	-	125,128
Winter (M+S):					
225/55 R 16 95H S	td -	7J x 16 H2	20	-	50,115,134
225/50 R 17 94H Std/RS	С -	7½J x 17 EH2	20	-	116,138
245/45 R 17 95V 1) RS	C -	8J x 17 EH2	20	-	122,144
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

Baureihe 5 (E60) - Limousine

545i/iA (N62)					
Reifendimension	Stahlscheiben-		IS	Styling Nr.	
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/50 R 17 94W Std/	RSC -	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC -	8J x 17 EH2	20	-	122,144
245/40 R 18 93Y 1)	RSC -	8J x 18 EH2	20	-	32,71,89,123,124,129
18"-Mischbereifung: 1)					
VA: 245/40 R 18 93Y	RSC -	8J x 18 EH2	20	-	32,89,124
HA: 275/35 R 18 95Y	RSC -	9J x 18 EH2	32	-	32,89,124
19"-Mischbereifung: 1)					
VA: 245/35 R 19 93Y XL	Std -	8J x 19 EH2	20	-	101,125,128
HA: 275/30 R 19 96Y XL	Std -	9½J x 19 EH2	32	-	101,125,128
VA: 245/35 R 19 93Y XL	RSC -	8½J x 19 EH2	18	-	125,128
HA: 275/30 R 19 96Y XL	RSC -	9½J x 19 EH2	32	-	125,128
Winter (M+S):					
225/50 R 17 94H Std/	RSC -	7½J x 17 EH2	20	-	116,138
245/45 R 17 95V 1)	RSC -	8J x 17 EH2	20	-	122,144
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

Baureihe 5 (E61)

525i/iA (M54)	525i/iA (M54)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Sty	Styling Nr.	
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM	
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129	
Winter (M+S):							
225/55 R 16 95Q/T/H	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94Q/T/H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95Q/T/H 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/45 R 17 99V XL 1) 2)	RSC	-	8J x 17 EH2	20	-	122,144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E61)

525d/dA (M57)	525d/dA (M57)						
Reifendimension				IS	Sty	ling Nr.	
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM	
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/40 R 18 93W 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129	
Winter (M+S):							
225/55 R 16 95Q/T/H	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94Q/T/H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95Q/T/H 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/45 R 17 99V XL 1) 2)	RSC	-	8J x 17 EH2	20	-	122,144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E61)

530d/dA (M57)	530d/dA (M57)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM	
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129	
Winter (M+S):							
225/55 R 16 95Q/T/H	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94Q/T/H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95Q/T/H 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/45 R 17 99V XL 1) 2)	RSC	-	8J x 17 EH2	20	-	122,144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E61)

545i/iA (N62)	545i/iA (N62)						
Reifendimension		Stahlscheiben- Leich		IS	Styling Nr.		
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM	
Sommer:							
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95Y 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129	
Winter (M+S):							
225/50 R 17 94Q/T/H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95Q/T/H 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/45 R 17 99V XL 1) 2)	RSC	-	8J x 17 EH2	20	-	122,144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E60) - Limousine

520i/iA (M54B22), 523	Bi/iA (N5	2B25UL)				
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.	
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
225/55 R 16 95V	Std	-	7J x 16 H2	20	-	50,115,134
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144
245/40 R 18 93W 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2	20	-	32,89,124
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2	32	-	32,89,124
19"-Mischbereifung: 1)						
VA: 245/35 ZR 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128
HA: 275/30 ZR 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128
VA: 245/35 R 19 93Y XL	RSC	-	8½J x 19 EH2	18	-	125,128
HA: 275/30 R 19 96Y XL	RSC	-	9½J x 19 EH2	32	-	125,128
Winter (M+S):						
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95H,V 1)	RSC	-	8J x 17 EH2	20	-	122,144
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E60) - Limousine

525i/iA (M54B25)	525i/iA (M54B25)						
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:							
225/55 R 16 95W St	d -	7J x 16 H2	20	-	50,115,134		
225/50 R 17 94W Std/RS0	C -	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95W 1) RSG	C -	8J x 17 EH2	20	-	122,144		
245/40 R 18 93W 1) RSG	C -	8J x 18 EH2	20	-	32,71,89,123,124,129		
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W RSG	C -	8J x 18 EH2	20	-	32,89,124		
HA: 275/35 R 18 95W RSG	C -	9J x 18 EH2	32	-	32,89,124		
19"-Mischbereifung: 1)							
VA: 245/35 ZR 19 93Y XL St	d -	8J x 19 EH2	20	-	101,125,128		
HA: 275/30 ZR 19 96Y XL St	d -	9½J x 19 EH2	32	-	101,125,128		
VA: 245/35 R 19 93Y XL RSG	C -	8½J x 19 EH2	18	-	125,128		
HA: 275/30 R 19 96Y XL RSG	C -	9½J x 19 EH2	32	-	125,128		
Winter (M+S):							
225/55 R 16 95H St	d 7J x 16 H2	7J x 16 H2	20	12	50,115,134		
225/50 R 17 94H Std/RSG	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95H,V 1) RSG	C -	8J x 17 EH2	20	-	122,144		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E60) - Limousine

525i/iA (N52B25OL)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Stylin	ng Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/55 R 16 95W St	d -	7J x 16 H2	20	-	50,115,134
225/50 R 17 94W Std/RS0	C -	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1) RSG	C -	8J x 17 EH2	20	-	122,144
245/40 R 18 93W 1) RSG	C -	8J x 18 EH2	20	-	32,71,89,123,124,129
18"-Mischbereifung: 1)					
VA: 245/40 R 18 93W RSG	C -	8J x 18 EH2	20	-	32,89,124
HA: 275/35 R 18 95W RSG	C -	9J x 18 EH2	32	-	32,89,124
19"-Mischbereifung: 1)					
VA: 245/35 ZR 19 93Y XL St	d -	8J x 19 EH2	20	-	101,125,128
HA: 275/30 ZR 19 96Y XL Ste	d -	9½J x 19 EH2	32	-	101,125,128
VA: 245/35 R 19 93Y XL RSG	C -	8½J x 19 EH2	18	-	125,128
HA: 275/30 R 19 96Y XL RSG	C -	9½J x 19 EH2	32	-	125,128
Winter (M+S):					
225/55 R 16 95H St	d -	7J x 16 H2	20	-	50,115,134
225/50 R 17 94H Std/RS0	C -	7½J x 17 EH2	20	-	116,138
245/45 R 17 95H,V 1) RSG	-	8J x 17 EH2	20	-	122,144
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

Baureihe 5 (E60) - Limousine

	525d/dA (M57D25TÜ), 530d/dA (M57D30TÜ), 530d/dA (M57D30TÜ2), 530i/iA (M54B30), 530i/iA (N52B30)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.					
	ŀ	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM				
Sommer:										
225/55 R 16 95W	Std -		7J x 16 H2	20	-	50,115,134				
225/50 R 17 94W Std/l	RSC -	-	7½J x 17 EH2	20	-	116,138				
245/45 R 17 95W 1)	RSC -		8J x 17 EH2	20	-	122,144				
245/40 R 18 93W 1)	RSC -		8J x 18 EH2	20	-	32,71,89,123,124,129				
18"-Mischbereifung: 1)										
VA: 245/40 R 18 93W	RSC -	-	8J x 18 EH2	20	-	32,89,124				
HA: 275/35 R 18 95W	RSC -	-	9J x 18 EH2	32	-	32,89,124				
19"-Mischbereifung: 1)										
VA: 245/35 ZR 19 93Y XL	Std -		8J x 19 EH2	20	-	101,125,128				
HA: 275/30 ZR 19 96Y XL	Std -		9½J x 19 EH2	32	-	101,125,128				
VA: 245/35 R 19 93Y XL	RSC -	-	8½J x 19 EH2	18	-	125,128				
HA: 275/30 R 19 96Y XL	RSC -	-	9½J x 19 EH2	32	-	125,128				
Winter (M+S):										
225/55 R 16 95H	Std -	-	7J x 16 H2	20	-	50,115,134				
225/50 R 17 94H Std/l	RSC -	-	7½J x 17 EH2	20	-	116,138				
245/45 R 17 95H,V 1)	RSC -		8J x 17 EH2	20	_	122,144				
Reserverad:										
T 135/80 R 17 102M 1)	4	4.00B x 17 H2	-	18	12	-				

Baureihe 5 (E60) - Limousine

535dA (M57 TOP), 54	5i/iA (N	62)				
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Stylin	ng Nr.
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2	20	-	32,89,124
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2	32	-	32,89,124
19"-Mischbereifung: 1)						
VA: 245/35 Z R 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128
HA: 275/30 Z R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128
VA: 245/35 R 19 93Y XL	RSC	-	8½J x 19 EH2	18	-	125,128
HA: 275/30 R 19 96Y XL	RSC	-	9½J x 19 EH2	32	-	125,128
Winter (M+S):						
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95H,V 1)	RSC	-	8J x 17 EH2	20	-	122,144
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E60) - Allrad Limousine

525xi/xiA (N52B25O	525xi/xiA (N52B25OL), 530xi/xiA (N52B30)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Stylin	ng Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM				
Sommer:										
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	43	-	138				
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	43	-	122				
245/40 R 18 93W 1)	RSC	-	8J x 18 EH2	43	-	123,124				
18"-Mischbereifung: 1)										
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2	43	-	124				
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2	55	-	124				
Winter (M+S):										
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	43	-	138				
245/45 R 17 95H,V 1)	RSC	-	8J x 17 EH2	43	-	122				
Reserverad:										
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-				

Technisch mögliche Rad-/Reifenkombinationen MJ '2005 E60 M-Sportpaket

Standardantrieb							
Reifendimension	Leichtmetall-	IS	Stylir	ng Nr.			
	Rad (LM-Rad)	mm	St.	LM			
Sommer:							
Mischbereifung: 1)							
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M			
VA: 245/35 R 19 4)	8,5 x 19	18	-	172M			
HA: 275/30 R 19 4)	9,5J x 19	32	-	172M			
Winter (M+S):							
s.AG							

Allrad								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M				
Winter (M+S):								
s.AG								

E60 M5 Limousine	E60 M5 Limousine								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.					
	Rad (LM-Rad)	mm	St.	LM					
Sommer:									
Mischbereifung: 1) 2)									
VA: 255/40 ZR 19	8,5J x 19	12	-	166M					
HA: 285/35 ZR 19	9,5J x 19	28	-	166M					
VA: 255/40 ZR 19	8,5J x 19	12	-	167M					
HA: 285/35 ZR 19	9,5J x 19	28	-	167M					
Winter (M+S):									
VA: 245/45 R 18	8J x 18	14	-	184M					
HA: 245/45 R 18	8J x 18	14	-	184M					
Reserverad:									
3)	-	-	-	-					

Baureihe 5 (E61) - Touring

523i/iA (N52)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.	
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM
Sommer:						
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129
Winter (M+S):						
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95H 1) 245/45 R 17 99V XL 1) 2)	RSC RSC	-	8J x 17 EH2	20	-	122,144
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E61) - Touring

525i/iA (M54)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.	
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM
Sommer:						
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129
Winter (M+S):						
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95H 1) 245/45 R 17 99V XL 1) 2)	RSC RSC	-	8J x 17 EH2	20	-	122,144
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E61) - Touring

525d/dA (M57)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.	
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM
Sommer:						
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144
245/40 R 18 93W 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129
Winter (M+S):						
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138
245/45 R 17 95H 1) 245/45 R 17 99V XL 1) 2)	RSC RSC	-	8J x 17 EH2	20	ı	122,144
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E61) - Touring

525i/iA (N52), 530i/iA (N52), 530d/dA (M57)							
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM	
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	20	-	122,144	
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129	
Winter (M+S):							
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 R 17 95H 1) 245/45 R 17 99V XL 1) 2)	RSC RSC	-	8J x 17 EH2	20	-	122,144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E61) - Touring

545i/iA (N62), 535dA (M	545i/iA (N62), 535dA (M57 TOP)							
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
		Rad (StRad)	Rad (LM- Rad)	mm	St.	LM		
Sommer:								
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95Y 1)	RSC	-	8J x 17 EH2	20	-	122,144		
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129		
Winter (M+S):								
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95H 1) 245/45 R 17 99V XL 1) 2)	RSC RSC	-	8J x 17 EH2	20	-	122,144		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E61) - Allrad Touring

525xi/xiA (N52)						
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Stylin	ng Nr.
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	43	-	138
245/45 R 17 95W 1)	RSC	-	8J x 17 EH2	43	-	122
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	43	-	123,124
Winter (M+S):						
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	43	=	138
245/45 R 17 95H 1)	RSC					
245/45 R 17 99V XL 1) 2)	RSC	-	8J x 17 EH2	43	-	122
		_				
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E61) - Allrad Touring

530xi/xiA (N52)							
Reifendimension				IS	Stylin	ıg Nr.	
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	43	-	138	
245/45 R 17 95Y 1)	RSC	-	8J x 17 EH2	43	-	122	
245/40 R 18 93Y 1)	RSC	-	8J x 18 EH2	43	-	123,124	
Winter (M+S):							
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	43	-	138	
245/45 R 17 95H 1)	RSC						
245/45 R 17 99V XL 1) 2)	RSC	-	8J x 17 EH2	43	-	122	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Technisch mögliche Rad-/Reifenkombinationen MJ '2005 E61 M-Sportpaket

Standardantrieb								
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS	Stylin	ng Nr.				
		mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M				
Winter (M+S):								
s.AG								

Allrad								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M				
Winter (M+S):								
s.AG								

Technisch mögliche Rad-/Reifenkombinationen MJ '2005 E60 / E61 BMW Individual

Standardantrieb								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i				
Winter (M+S):								
s.AG								

Allrad								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i				
Winter (M+S):								
s.AG								

Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	S Styling Nr.			
remendamension		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:								
225/55 R 16 95V	Std	-	7J x 16 H2	20	-	50,115,134		
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144		
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	144		
245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	20	-	32,71,89,123,124,129,135M,152i		
18"-Mischbereifung: 1)								
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	20	-	32,89,124		
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	32	-	32,89,124		
19"-Mischbereifung: 1)								
VA: 245/35 R 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128		
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128		
VA: 245/35 R 19 93Y XL	RSC		8½J x 19 EH2	18	-	125,128,172M		
VA. 243/33 K 19 93 F AL	KSC	-	8½J x 19 EH2+	18	-	172M,179,190		
HA: 275/30 R 19 96Y XL	RSC		9½J x 19 EH2	32	-	125,128,172M		
III. 273/30 R 17 701 AE	RBC		9½J x 19 EH2+	32	-	172M,179,190		
Winter (M+S):								
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134		
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 D 17 00 V VI	DCC		8J x 17 EH2	20	-	122,144		
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	144		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	144	
245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	20	-	32,71,89,123,124,129,135M,152i	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	20	-	32,89,124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	32	-	32,89,124	
19"-Mischbereifung: 1)							
VA: 245/35 R 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128	
VA: 245/35 R 19 93Y XL	RSC		81/2J x 19 EH2	18	-	125,128,172M	
VII. 243/33 K 1) /31 AL	RSC		8½J x 19 EH2+	18	-	172M,179,190	
HA: 275/30 R 19 96Y XL	RSC	_	9½J x 19 EH2	32	-	125,128,172M	
III. 275/50 K 17 701 AL	RSC		9½J x 19 EH2+	32	-	172M,179,190	
Winter (M+S):							
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 D 17 00 V VI	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	S Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	144	
245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	20	-	32,71,89,123,124,129,135M,152i	
18"-Mischbereifung: 1)				<u> </u>			
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	20	-	32,89,124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	32	-	32,89,124	
19"-Mischbereifung: 1)				<u> </u>			
VA: 245/35 R 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128	
111 A45/25 D 10 001/11	Pag		8½J x 19 EH2	18	-	125,128,172M	
VA: 245/35 R 19 93Y XL	RSC	-	8½J x 19 EH2+	18	-	172M,179,190	
HA: 275/30 R 19 96Y XL	RSC		9½J x 19 EH2	32	-	125,128,172M	
na. 2/3/30 K 19 90 F AL	KSC	-	9½J x 19 EH2+	32	-	172M,179,190	
Winter (M+S):							
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
245/45 D 17 00 V VI	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	144	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E60) - Limousine

535dA (M57D30TOI	535dA (M57D30TOP), 540i/iA (N62B40), 550i/iA (N62B48)								
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:									
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	20	-	116,138			
245/45 R 17 95W	RSC		8J x 17 EH2	20	-	122,144			
243/43 K 1 / 93 W	KSC	-	8J x 17 EH2+	20	-	144			
245/40 R 18 93Y	RSC	-	8J x 18 EH2/EH2+	20	-	32,71,89,123,124,129,135M,152i			
18"-Mischbereifung: 1)									
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2/EH2+	20	-	32,89,124			
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2/EH2+	32	-	32,89,124			
19"-Mischbereifung: 1)									
VA: 245/35 R 19 93Y XL	Std	-	8J x 19 EH2	20	-	101,125,128			
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128			
MA. 245/25 D 10 02W M	ngg		8½J x 19 EH2	18	-	125,128,172M			
VA: 245/35 R 19 93Y XL	RSC	-	8½J x 19 EH2+	18	-	172M,179,190			
HA: 275/30 R 19 96Y XL	RSC		9½J x 19 EH2	32	-	125,128,172M			
HA. 2/3/30 K 19 901 AL	KSC	-	9½J x 19 EH2+	32	-	172M,179,190			
Winter (M+S):									
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138			
245/45 R 17 99 V XL	RSC		8J x 17 EH2	20	-	122,144			
243/43 K I / 99 V AL	KSC	-	8J x 17 EH2+	20	-	144			
Reserverad:									
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-			

Baureihe 5 (E60) - Allrad Limousine

525xi/xiA (N52B25C	525xi/xiA (N52B25OL), 530xi/xiA (N52B30), 530xd/xdA (M57D30)								
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:									
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	43	-	138			
245/45 R 17 95W	RSC	-	8J x 17 EH2	43	-	122			
245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	43	-	123,124,135M,152i			
18"-Mischbereifung: 1)									
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	43	-	124			
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	55	-	124			
Winter (M+S):									
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	43	-	138			
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2	43	-	122			
Reserverad:									
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-			

Technisch mögliche Rad-/Reifenkombinationen MJ 2006 E60 M-Sportpaket

Standardantrieb	Standardantrieb								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.					
	Rad (LM-Rad)	mm	St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M					
VA: 245/35 R 19 4)	8,5 x 19	18	-	172M					
HA: 275/30 R 19 4)	9,5J x 19	32	-	172M					
Winter (M+S):									
s.AG									

Allrad					
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.	
			St.	LM	
Sommer:					
Mischbereifung: 1)					
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M	
Winter (M+S):					
s.AG					

E60 M5 Limousine				
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.
			St.	LM
Sommer:				
Mischbereifung: 1) 2)				
VA: 255/40 ZR 19	8,5J x 19	12	-	166M
HA: 285/35 ZR 19	9,5J x 19	28	-	166M
VA: 255/40 ZR 19	8,5J x 19	12	-	167M
HA: 285/35 ZR 19	9,5J x 19	28	-	167M
Winter (M+S):				
VA: 245/45 R 18	8J x 18	14	-	184M
HA: 245/45 R 18	8J x 18	14	-	184M
Reserverad:				
3)	-	-	-	-

Baureihe 5 (E61) - Touring

520d (M47), 523i/iA (N52)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
	Rad (StRad)	Rad (LM- Rad)	mm	St.	LM		
Sommer:							
225/55 R 16 95W Std		7J x 16 H2	20	-	50,115,134		
225/50 R 17 94W Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144		
	-	8J x 17 EH2+	20	-	144		
245/40 R 18 93W RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
	-	8J x 18 EH2+	20	-	32,71,89,123,124,129,135M,152i		
Winter (M+S):							
225/55 R 16 95H Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134		
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2	20	-	122,144		
		8J x 17 EH2+	20	-	144		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E61) - Touring

525d/dA (M57)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
	Rad (StRad) Rad (LM-Rad)		mm	St.	LM		
Sommer:							
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134		
225/50 R 17 94W Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144		
	-	8J x 17 EH2+	20	-	144		
245/40 R 18 93W RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
		8J x 18 EH2+	20	-	32,71,89,123,124,129,135M,152i		
Winter (M+S):							
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134		
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2	20	-	116,138		
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2	20	-	122,144		
		8J x 17 EH2+	20	-	144		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E61) - Touring

525i/iA (N52), 530i/iA (N52	525i/iA (N52), 530i/iA (N52), 530d/dA (M57)										
Reifendimension	Stahlscheiben-				ling Nr.						
	Rad (StRad)	Rad (LM- Rad)	mm	St.	LM						
Sommer:											
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134						
225/50 R 17 94Y Std/RSC	-	7½J x 17 EH2	20	-	116,138						
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144						
243/43 K 1 / 93 W KSC	=	8J x 17 EH2+	20	=	144						
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i						
243/40 K 18 93 I KSC	_	8J x 18 EH2+	20	-	32,71,89,123,124,129,135M,152i						
Winter (M+S):											
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134						
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2	20	-	116,138						
245/45 D 17 00V VI 2) DCC		8J x 17 EH2	20	-	122,144						
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	144						
Reserverad:											
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-						

Baureihe 5 (E61) - Touring

535dA (M57 TOP), 550i/iA	535dA (M57 TOP), 550i/iA (N62)									
Reifendimension	Stahlscheiben-			Styling Nr.						
	Rad (StRad)	Rad (LM- Rad)	mm	St.	LM					
Sommer:										
225/50 R 17 94Y Std/RSC	-	7½J x 17 EH2	20	-	116,138					
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144					
243/43 K 1 / 93 1 KSC	=	8J x 17 EH2+	20	-	144					
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i					
243/40 K 18 93 1 KSC	-	8J x 18 EH2+	20	-	32,71,89,123,124,129,135M,152i					
Winter (M+S):										
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2	20	-	116,138					
245/45 D 17 00V VI 2) DCC		8J x 17 EH2	20	-	122,144					
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	144					
Reserverad:										
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-					

Baureihe 5 (E61) - Allrad Touring

525xi/xiA (N52)						
Reifendimension		II II		IS	Stylii	ıg Nr.
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	43	-	138
245/45 R 17 95W	RSC	-	8J x 17 EH2	43	-	122
245/40 R 18 93Y	RSC	_	8J x 18 EH2	43	-	123,124,135M,152i
243/40 K 18 93 I	KSC	-	8J x 18 EH2+	43	-	123,124,135M,152i
Winter (M+S):						
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	43	-	138
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2	43	-	122
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E61) - Allrad Touring

530xi/xiA (N52), 530x	xd/xdA (N	I 57)						
Reifendimension				IS	Stylii	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:								
225/50 R 17 94Y	Std/RSC	-	7½J x 17 EH2	43	-	138		
245/45 R 17 95Y	RSC	-	8J x 17 EH2	43	-	122		
245/40 R 18 93Y	RSC	-	8J x 18 EH2	43	-	123,124,135M,152i		
243/40 K 18 93 I	KSC	-	8J x 18 EH2+	43	-	123,124,135M,152i		
Winter (M+S):								
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	43	-	138		
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2	43	-	122		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

Technisch mögliche Rad-/Reifenkombinationen MJ 2006 E61 M-Sportpaket

Standardantrieb									
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.					
	Rad (LM-Rad)	mm	St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M					
Winter (M+S):									
s.AG		·							

Allrad									
Reifendimension	Leichtmetall-	IS	Stylii	ng Nr.					
	Rad (LM-Rad)	mm	St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M					
Winter (M+S):									
s.AG									

Technisch mögliche Rad-/Reifenkombinationen MJ '2006 E60 / E61 BMW Individual

Standardantrieb	Standardantrieb Standardantrieb									
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.						
	Rad (LM-Rad)	mm	St.	LM						
Sommer:										
Mischbereifung: 1)										
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i						
Winter (M+S):										
s.AG										

Allrad									
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.					
	Rad (LM-Rad)	mm	St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i					
Winter (M+S):									
s.AG									

Baureihe 5 (E60) - Limousine

520d/dA (M47D20O	L), 523i/i		•	т —	т —		
Reifendimension		Stahlscheiben- Rad (StRad)	Leichtmetall- Rad (LM-Rad)	IS mm	Styling Nr.		
		Kau (StKau)	Rau (Livi-Rau)	111111	St.	LM	
Sommer:							
225/55 R 16 95V	Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 R 17 94W	Std/RSC		7½J x 17 EH2	20	-	116,138	
223/30 K 1 / 94 W	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 95W	RSC		8J x 17 EH2	20	-	122,144	
243/43 K 1 / 93 W	KSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 93W	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 93 W	KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
				<u> </u>			
18"-Mischbereifung: 1)			<u> </u>				
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2	20	-	32,89,124	
			8J x 18 EH2+	20	-	32,124,247	
HA: 275/35 R 18 95W	RSC	_	9J x 18 EH2	32	-	32,89,124	
			9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i	
HA: 275/30 R 19 96Y XL	Std	_	9½J x 19 EH2	32	-	101,125,128,172M	
			9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):							
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242	
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242	
225/50 D 15 04H	G: 1/D.C.C		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 00 W W	DOC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 P 10 07 ****	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E60) - Limousine

525i/iA (N52B25OL), 525i/iA (N53B30UL), 525d/dA (M57D25TÜ), 525d/dA (M57D30UL)								
Reifendimension		Stahlscheiben- Leichtmetall-		IS	Styling Nr.			
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:								
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134,242		
225/50 P 17 04W	Ct 1/D C C		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244		
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144		
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245		
245/40 D 19 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
18"-Mischbereifung: 1)								
MA. 245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,89,124		
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,247		
HA. 275/25 D 10 05W	DCC		9J x 18 EH2	32	-	32,89,124		
HA: 275/35 R 18 95W	RSC	<u> </u>	9J x 18 EH2+	32	-	32,124,247		
19"-Mischbereifung: 1)								
			8J x 19 EH2	20	-	101,125,128		
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M		
			8½J x 19 EH2+	18	-	128,172M,179,190,228i		
IIA. 275/20 D 10 0/W VI	Ct1		9½J x 19 EH2	32	-	101,125,128,172M		
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i		
Winter (M+S):								
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242		
225/50 D 17 04H	Gt 1/D.C.C.		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244		
245/45 D 17 00 M N/I	RSC		8J x 17 EH2	20	-	122,144		
245/45 R 17 99 V XL	KSC	-	8J x 17 EH2+	20	-	122,245		
245/40 D 10 07 V VI	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
245/40 R 18 97 V XL	KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

Baureihe 5 (E60) - Limousine

530d/dA (M57D30),	530d/dA (M57D30), 530i/iA (N52B30)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ing Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM				
Sommer:										
225/50 D 17 04W	Ct 1/D.C.C		7½J x 17 EH2	20	-	116,138				
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244				
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144				
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245				
245/40 D 19 02W	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i				
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247				
18"-Mischbereifung: 1)										
VA: 245/40 R 18 93W	RSC		8J x 18 EH2	20	-	32,89,124				
VA. 243/40 K 18 33 W	KSC	-	8J x 18 EH2+	20	-	32,124,247				
HA: 275/35 R 18 95W	RSC	SC -	9J x 18 EH2	32	-	32,89,124				
HA: 2/3/33 K 18 93 W	KSC		9J x 18 EH2+	32	-	32,124,247				
19"-Mischbereifung: 1)										
			8J x 19 EH2	20	-	101,125,128				
VA: 245/35 R 19 93Y XL	Std	Std -	8½J x 19 EH2	18	-	125,128,172M				
			8½J x 19 EH2+	18	-	128,172M,179,190,228i				
IIA. 275/20 D 10 0/W VI	Std		9½J x 19 EH2	32	-	101,125,128,172M				
HA: 275/30 R 19 96Y XL	Sia	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i				
Winter (M+S):										
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242				
225/50 D 17 04H	Ct 1/D.C.C		7½J x 17 EH2	20	-	116,138				
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244				
045/45 D 45 00 M M	DCC		8J x 17 EH2	20	-	122,144				
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245				
245/40 D 10 07 V VI	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i				
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247				
Reserverad:										
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-				

Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	S Styling Nr.		
Renemension		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/50 D 15 0 4W	g, 1/p.g.g		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 05W	ngg		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
			8J x 18 EH2	20	-	32,89,124	
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,247	
114 075/25 D 10 05W	pag		9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	1	125,128,172M	
			8½J x 19 EH2+	18	•	128,172M,179,190,228i	
HA: 275/30 R 19 96Y XL	Std		9½J x 19 EH2	32	-	101,125,128,172M	
HA. 275/30 K 19 901 AL	Siu	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):							
005/50 D 45 04Y	g. Imag		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 P 17 00 M W	D.C.C.		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 D 10 07 V VI	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ing Nr.
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
225/50 D 17 04W	C44/DCC		7½J x 17 EH2	20	-	116,138
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 05W	RSC		8J x 17 EH2	20	-	122,144
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245
245/40 D 19 02V	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152
245/40 R 18 93Y	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
18"-Mischbereifung: 1)						
	D.C.C.		8J x 18 EH2	20	-	32,89,124
VA: 245/40 R 18 93Y RSC	RSC	-	8J x 18 EH2+	20	-	32,124,247
HA. 275/25 B 10 05X	D.C.C.		9J x 18 EH2	32	-	32,89,124
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2+	32	-	32,124,247
19"-Mischbereifung: 1)						
			8J x 19 EH2	20	-	101,125,128
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M
			8½J x 19 EH2+	18	-	128,172M,179,190,228i
HA: 275/30 R 19 96Y XL	Std		9½J x 19 EH2	32	-	101,125,128,172M
11A. 275/50 K 19 901 AL	Siu		9½J x 19 EH2+	32	-	128,172M,179,190,228i
Winter (M+S):						
005/50 P 45 0 47	a imaa		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 00 M WI	DCC		8J x 17 EH2	20	-	122,144
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245
245/40 D 10 07 V VI	BCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ing Nr.	
		Rad (StRad)	Rad (LM-Rad)	mm		LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
225/50 B 17 04W	C+1/DCC		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245	
245/45 D 17 05W	RSC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 93Y	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 93 I	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
<u> </u>		-	8J x 18 EH2	20	_	32,89,124	
VA: 245/40 R 18 93Y RSC	RSC		8J x 18 EH2+	20	-	32,124,247	
			9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95Y	RSC	RSC -	9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
1) 11100110 010110111g. 1)			8J x 19 EH2	20	 	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	_	125,128,172M	
	~~~		8½J x 19 EH2+	18	-	128,172M,179,190,228i	
			9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):							
	~		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
045/45 D 45 00 35	-~-		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 D 10 07 V VI	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Allrad Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/50 R 17 94W	Std/RSC		7½J x 17 EH2	43	-	138	
223/30 K 1 / 94 W	Std/RSC	-	7½J x 17 EH2+	43	-	138,243	
245/45 R 17 95W	RSC	-	8J x 17 EH2/EH2+	43	-	122	
0.45/40 P 40.00W	RSC		8J x 18 EH2	43	-	123,124,135M,152i	
245/40 R 18 93W	KSC	-	8J x 18 EH2+	43	-	124,135M,152i,246	
18"-Mischbereifung: 1)						<del> </del>	
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	43	-	124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	55	-	124	
Winter (M+S):							
	~ 4 - ~ ~		7½J x 17 EH2	43	-	138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43		138,243	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2/EH2+	43	-	122	
245/40 D 10 07 W W	DCC		8J x 18 EH2	43	-	123,124,135M,152i	
245/40 R 18 97 V XL	5/40 R 18 97 V XL RSC -		8J x 18 EH2+	43	-	124,135M,152i,246	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Allrad Limousine

530xd/xdA (M57D30 Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
Renenulmension		Rad (StRad)	Rad (LM-Rad)	mm	Styling Nr. St. LM			
0					St.	Livi		
Sommer:								
225/50 R 17 94W	Std/RSC	_	7½J x 17 EH2	43	-	138		
	514/1150		7½J x 17 EH2+	43	-	138,243		
245/45 R 17 95W	RSC	-	8J x 17 EH2/EH2+	43	-	122		
245/40 R 18 93Y	RSC		8J x 18 EH2	43	-	123,124,135M,152i		
243/40 K 18 93 f	KSC	-	8J x 18 EH2+	43	-	124,135M,152i,246		
18"-Mischbereifung: 1)								
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2/EH2+	43	-	124		
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2/EH2+	55	-	124		
Winter (M+S):								
225/50 P 17 04H	G. I/D.C.C.		7½J x 17 EH2	43	-	138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43		138,243		
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2/EH2+	43	-	122		
245/40 D 10 07 N VI	ngg		8J x 18 EH2	43	-	123,124,135M,152i		
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	43	-	124,135M,152i,246		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	1-	18	12	-		

### Technisch mögliche Rad-/Reifenkombinationen MJ 2007 E60 M-Sportpaket

Standardantrieb								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M				
VA: 245/35 R 19 4)	8,5 x 19	18	-	172M				
HA: 275/30 R 19 4)	9,5J x 19	32	-	172M				
Winter (M+S):								
s.AG								

Allrad									
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.					
			St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M					
Winter (M+S):									
s.AG									

### Technisch mögliche Rad-/Reifenkombinationen MJ 2007 E60 BMW Individual

Standardantrieb								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i				
VA: 245/35 R 19 4)	8,5J x 19	18	-	228i				
HA: 275/30 R 19 4)	9,5J x 19	32	-	228i				
Winter (M+S):								
s.AG								

Allrad								
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS	Stylin	ng Nr.				
		mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i				
Winter (M+S):								
s.AG								

# Baureihe 5 (E61) - Touring

520d (M47D20), 523i/iA (	N52B25UL), 5	523i/iA (N53B2	25UL	4)		
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:						
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242	
235/50 D 17 04W		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94W Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144	
243/43 K 1 / 93 W KSC	=	8J x 17 EH2+	20	-	122,245	
245/40 R 18 93W RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 16 93 W KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M	
1) KSC	=	8½J x 19 EH2+	18	-	172M,179,190,228i	
Winter (M+S):						
225/55 R 16 95H Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242	
225/50 D 17 04H		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 00V VI 2) DSC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 97 V XL RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
2) RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:						
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E61) - Touring

525d/dA (M57D25), 525d	/dA (M57D30)	UL)				
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:						
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 R 17 94W Std/RSC		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94W Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144	
243/43 K I / 93 W KSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 93W RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 93 W KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M	
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i	
Winter (M+S):						
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 R 17 94H Std/RSC		7½J x 17 EH2	20	-	116,138	
223/30 K 1 / 94H Sta/KSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 00V VI 2) DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 97 V XL RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
2) KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:						
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E61) - Touring

525i/iA (N52B25OL),	525i/iA (N53H	330UL)				
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:						
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 R 17 Std/RSC		7½J x 17 EH2	20	-	116,138	
94Y Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144	
243/43 K 1 / 93 W KSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 93 1 KSC	=	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
245/35 R 19 RSC		8½J x 19 EH2	18	-	125,128,172M	
93Y XL 1) RSC	-	8½J x 19 EH2+	18	-	172M,179,190,228i	
Winter (M+S):						
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 R 17		7½J x 17 EH2	20	-	116,138	
94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 99V		8J x 17 EH2	20	-	122,144	
XL 2) RSC	-	8J x 17 EH2+	20	-	122,245	
245/40 R 18 97 V		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
XL 2) RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:						
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E61) - Touring

530d/dA (M57D30)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/50 R 17 Std/RSC		7½J x 17 EH2	20	-	116,138
94Y Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144
243/43 K 1 / 93 W KSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 18 93 1 KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 RSC		8½J x 19 EH2	18	-	125,128,172M
93Y XL 1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i
Winter (M+S):					
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242
225/50 R 17		7½J x 17 EH2	20	-	116,138
94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 99V RSC		8J x 17 EH2	20	-	122,144
XL 2)	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 97 V		8J x 18 EH2	20	ı	32,71,89,123,124,129,135M,152i
XL 2)	-	8J x 18 EH2+	20	ı	32,124,135M,152i,246,247
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

530i/iA (N52B30)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/50 R 17 94Y Std/RSC		7½J x 17 EH2	20	-	116,138
223/30 K 1/ 941 Sta/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144
2+3/+3 K 17 /31 KGC		8J x 17 EH2+ 20 8J x 18 EH2 20 8J x 18 EH2+ 20 8½J x 19 EH2 18	20	-	122,245
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 16 93 1 KSC		8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M
1)		8½J x 19 EH2+	18	-	172M,179,190,228i
Winter (M+S):					
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242
225/50 D 17 04H		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 99V XL 2) RSC		8J x 17 EH2	20	-	122,144
243/43 R 1 / 99 V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 97 V XL RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
2) RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

530i/iA (N53B30OL)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/50 R 17 94Y Std/RSC		7½J x 17 EH2	20	-	116,138
223/30 K 1/ 94 Y Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144
243/43 K 17 93 1 KSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 18 93 I KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i
Winter (M+S):					
225/50 R 17 94H Std/RSC		7½J x 17 EH2	20	-	116,138
223/30 K 1 / 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 99V XL 2) RSC		8J x 17 EH2	20	-	122,144
243/43 K 1 / 99 V AL 2) KSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 97 V XL RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
2) KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

535dA (M57D30TOP)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/50 R 17 94Y Std/RSC		7½J x 17 EH2	20	-	116,138
223/30 K 1/ 94 Y Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144
243/43 K 17 93 1 KSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 18 93 1 KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i
Winter (M+S):					
225/50 R 17 94H Std/RSC		7½J x 17 EH2	20	-	116,138
223/30 K 1 / 94H Std/RSC	-	7½J x 17 EH2+	20	-	32,71,89,123,124,129,135M,153 32,124,135M,152i,246,247 125,128,172M 172M,179,190,228i 116,138 138,243,244
245/45 R 17 99V XL 2) RSC		8J x 17 EH2	20	-	122,144
243/43 K 1 / 99 V AL 2) KSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 97 V XL RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
2) KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

550i/iA (N62B48)					
Reifendimension	Stahlscheiben-	Leichtmetall-			ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
		7½J x 17 EH2	20	-	116,138
225/50 R 17 94Y Std/RSC		7½J x 17 EH2+	20	-	138,243,244
223/30 K 1 / 94 Y Std/RSC	-	8J x 17 EH2	20	-	122,144
		8J x 17 EH2+	20	-	122,245
245/45 D 17 05V DCC		8J x 17 EH2	20	-	122,144
245/45 R 17 95Y RSC	Rad (StRad)  Rad (StRad)  Rad (LM  7 ½ J x 17  7 ½ J x 17  8 J x 17 E  8 J x 17 E  8 J x 17 E  8 J x 18 E  8 J x 18 E  8 ½ J x 19  8 J x 17 E  8 J x 17 E  8 J x 18 E  8 J x 18 E  8 J x 18 E	8J x 17 EH2+	20	-	122,245
245/40 D 10 02W DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
245/40 R 18 93Y RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 93Y XL		8½J x 19 EH2	18	-	125,128,172M
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i
Winter (M+S):					
205/50 D 15 04H		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
045/45 D 17 001/1/1 0) DCC		8J x 17 EH2	20	-	122,144
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245
245/40 R 18 97 V XL		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
2) RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# **Baureihe 5 (E61) - Allrad Touring**

525xi/xiA (N52B25O	L), 525xi/	xiA (N53B30U	L), 525xd/xdA (M	157D3	<b>OUL</b>	)		
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
		Rad (StRad)	Rad (LM-Rad)	LM				
Sommer:								
225/50 D 17 04V	C+d/DCC		7½J x 17 EH2	43	-	138		
225/50 K 1 / 94 Y	5/50 R 17 94Y Std/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 R 17 95W	RSC	-	8J x 17 EH2/EH2+	43	-	122		
245/40 D 19 02W	DCC		8J x 18 EH2	43	-	123,124,135M,152i		
245/40 R 18 93Y	RSC	-	8J x 18 EH2+	43	-	124,135M,152i,246		
Winter (M+S):								
225/50 D 17 04H	G. 1/D.C.C.		7½J x 17 EH2	43	-	138		
225/50 R 17 94H	Std/RSC	-	Leichtmetall-  Rad (LM-Rad)   Min   Rad (LM-Rad)	43		138,243		
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2/EH2+	43	-	122		
245/40 D 10 07 M M 2)	DCC		8J x 18 EH2	43	-	123,124,135M,152i		
245/40 R 18 97 V XL 2)	RSC	-	8J x 18 EH2+	43	-	124,135M,152i,246		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

# **Baureihe 5 (E61) - Allrad Touring**

530xi/xiA (N52B30).	, 530xi/xi	A (N53B30OL	L), 530xd/xdA (M5	57D3(	))		
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	d) mm St. LM			
Sommer:							
225/50 R 17 94Y	Std/RSC		7½J x 17 EH2	43	-	138	
223/30 K 1/ 94 I	Sta/RSC	-	7½J x 17 EH2+	43	-	138,243	
245/45 R 17 95Y	RSC	-	8J x 17 EH2/EH2+	43	-	122	
245/40 R 18 93Y	RSC		8J x 18 EH2	43	-	123,124,135M,152i	
243/40 K 18 93 I	KSC	-	8J x 18 EH2+	43	-	123,124,135M,152i,246	
Winter (M+S):							
225/50 D 17 04H	G. 1/D.C.C		7½J x 17 EH2	43	-	138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43		138,243	
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2/EH2+	43	-	122	
245/40 D 10 07 N N 2	D.C.C.		8J x 18 EH2	43	-	123,124,135M,152i	
245/40 R 18 97 V XL 2)	RSC	-	8J x 18 EH2+	43	-	123,124,135M,152i,246	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

### Technisch mögliche Rad-/Reifenkombinationen MJ 2007 E61 M-Sportpaket

Standardantrieb						
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.		
	Rad (LM-Rad)	mm	St.	LM		
Sommer:						
Mischbereifung: 1)						
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M		
Winter (M+S):						
s.AG						

Allrad						
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.		
	Rad (LM-Rad)	mm	St.	LM		
Sommer:						
Mischbereifung: 1)						
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M		
Winter (M+S):						
s.AG						

### Technisch mögliche Rad-/Reifenkombinationen MJ 2007 E61 BMW Individual

Standardantrieb						
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.		
			St.	LM		
Sommer:						
Mischbereifung: 1)						
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i		
Winter (M+S):						
s.AG						

Allrad						
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.		
	Rad (LM-Rad)	mm	St.	LM		
Sommer:						
Mischbereifung: 1)						
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i		
Winter (M+S):						
s.AG						

E60 M5 Limousine	E60 M5 Limousine						
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.			
	Rad (LM-Rad)	mm	St.	LM			
Sommer:							
Mischbereifung: 1) 2)							
VA: 255/40 ZR 19	8,5J x 19	12	-	166M			
HA: 285/35 ZR 19	9,5J x 19	28	-	166M			
VA: 255/40 ZR 19	8,5J x 19	12	-	167M			
HA: 285/35 ZR 19	9,5J x 19	28	-	167M			
Winter (M+S):							
VA: 245/45 R 18	8J x 18	14	-	184M			
HA: 245/45 R 18	8J x 18	14	-	184M			
Reserverad:							
3)	-	-	-	-			

E61 M5 Touring					
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.	
	Rad (LM-Rad)	mm	St.	LM	
Sommer:					
Mischbereifung: 1) 2)					
VA: 255/40 ZR 19	8,5J x 19	12	-	166M	
HA: 275/35 ZR 19	9J x 19	17	-	166M	
VA: 255/40 ZR 19	8,5J x 19	12	-	167M	•
HA: 275/35 ZR 19	9J x 19	17	-	167M	•
Winter (M+S):					
VA: 245/45 R 18	8J x 18	14	-	184M	
HA: 245/45 R 18	8J x 18	14	-	184M	
Reserverad:					
3)	-	-	-	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS mm	Styl	ling Nr.
		Rad (StRad)	Rad (LM-Rad)		St.	_
Sommer:						
225/55 R 16 95V	Std	-	7J x 16 H2	20	-	50,115,134,242
			7½J x 17 EH2	20	-	116,138
			7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144
			8J x 17 EH2+	20	-	122,245,277,278
045/45 D 15 05W	Pag		8J x 17 EH2	20	-	122,144
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 D 10 02W			8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93W			8J x 18 EH2	20	- 32,89,124	32,89,124
	RSC	-	8J x 18 EH2+	20	-	32,124,247
HA: 275/35 R 18 95W	RSC -		9J x 18 EH2	32	-	32,89,124
		-	9J x 18 EH2+	32	-	32,124,247
19"-Mischbereifung: 1)						
			8J x 19 EH2	20	-	101,125,128
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M
			8½J x 19 EH2+	18	-	128,172M,179,190,228i
			9½J x 19 EH2	32	-	101,125,128,172M
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i
Winter (M+S):						
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242
225/50 P 15 04H	0.1/0.00		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H	Std/RSC		7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 00 V VI	RSC		8J x 17 EH2	20	-	122,144
245/45 R 17 99 V XL		-	8J x 17 EH2+	20	-	122,245,277,278
245/40 D 10 05 37 37	200	-	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152
245/40 R 18 97 V XL	RSC		8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E60) - Limousine

525i/iA (N52B25OL) Reifendimension		Stahlscheiben- Rad (StRad)	Leichtmetall-	IS	Styling Nr.		
Kenendiniension			Rad (LM-Rad)	mm	St.		
Sommer:			1		50.	<b>L</b> M	
225/55 R 16 95W	Std	_	7J x 16 H2	20	_	50,115,134,242	
			7½J x 17 EH2	20	-	116,138	
			7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
			8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
			8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W	200		8J x 18 EH2	20	32,89,124	32,89,124	
	RSC	-	8J x 18 EH2+	20	-	32,124,247	
055/05 D 40 05W	RSC	-	9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95W			9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	8J x 19 EH2 20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i	
HA. 275/20 D 10 06V VI	Std	-	9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL			9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):							
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 D 17 04H	~	-	7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC		7½J x 17 EH2+	20	-	138,243,244	
045/45 D 17 00 M M	RSC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL			8J x 17 EH2+	20	-	122,245,277,278	
245/40 D 10 07 X/X/	RSC	- 8J x 18 EH2 8J x 18 EH2+	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 97 V XL	RSC		8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben- Rad (StRad)	Leichtmetall- Rad (LM-Rad)	IS mm	Styling Nr.	
					St.	LM
Sommer:						
			7½J x 17 EH2	20	-	116,138
225/50 P 17 04W	Gr 1/D.C.C.		7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144
			8J x 17 EH2+	20	-	122,245,277,278
245/45 D 17 05W	ngc		8J x 17 EH2	20	-	122,144
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
18"-Mischbereifung: 1)						
VA: 245/40 R 18 93W	RSC		8J x 18 EH2	20	_	32,89,124
		-	8J x 18 EH2+	20	-	32,124,247
HA: 275/35 R 18 95W			9J x 18 EH2	32	-	32,89,124
	RSC	-	9J x 18 EH2+	32	-	32,124,247
10" Misslehausifan av 1)						
19"-Mischbereifung: 1)			01 10 5112	20		101 125 120
NA 045/25 D 10 02N NI	G. 1		8J x 19 EH2	20	-	101,125,128
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18 18	-	125,128,172M
			8½J x 19 EH2+ 9½J x 19 EH2	32	-	128,172M,179,190,228i 101,125,128,172M
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i
Winter (M+S):						, , , ,
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242
			7½J x 17 EH2	20	-	116,138
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
0.15/15 D 15 00			8J x 17 EH2	20	-	122,144
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 D 10 07 33 37	P.C.C.		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
205/50 P 17 0 4W	G. 1/D.C.C.		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
245/45 D 17 05W	ngg		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 P 10 02W	P.C.C.		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W			8J x 18 EH2	20	0 - 32.89.124	32,89,124	
	RSC	-	8J x 18 EH2+	20	-	32,124,247	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2	32	-	32,89,124	
			9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	- 125,128,172M	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i	
HA . 275/20 D 10 06V VI	Ct 1		9½J x 19 EH2	32	32 - 101	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):							
	~		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 02 V VV	Bac		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 D 10 07 V VI	BCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 97 V XL	RSC		8J x 18 EH2+	20		32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall- Rad (LM-Rad)	IS mm	Styling Nr.		
		Rad (StRad)			St.		
Sommer:							
			7½J x 17 EH2	20	-	116,138	
225/50 D 15 04W	0.1/200		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 D 10 023/	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93Y	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93Y	RSC		8J x 18 EH2	20	0 - 32,89,124	32,89,124	
	RSC		8J x 18 EH2+	20	-	32,124,247	
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2	32	-	32,89,124	
11A. 275/55 K 16 751			9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i	
IIA. 275/20 D 10 06V VI	CtJ		9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):							
225/50 P 17 04H	Ct1/DCC		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 00 V VI	RSC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL		-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 R 18 97 V XL	DSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 9/ V XL	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	. LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
225/50 B 17 04W	C44/DCC		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 R 18 93Y	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 93 I	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93Y			8J x 18 EH2	20	- 32.89.124	32,89,124	
	RSC	-	8J x 18 EH2+	20	-	32,124,247	
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2	32	-	32,89,124	
			9J x 18 EH2+	32	-	32,124,247	
10   Marthault (2 1)							
19"-Mischbereifung: 1)			01 10 5112	20		101 105 100	
114 045/25 P 10 001/11	a. 1		8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2	32	-	101,125,128,172M	
NV. 4 (NA+C)			9½J x 19 EH2+	32	-	128,172M,179,190,228i	
Winter (M+S):			51/1 15 PHO	20		116120	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2	20	-	116,138	
			7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
245/40 R 18 97 V XL	RSC	-	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
			8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Allrad Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/50 R 17 94W	Std/RSC		7½J x 17 EH2	43	-	138	
223/30 K 1 / 94 W	Std/RSC	-	7½J x 17 EH2+		-	138,243	
245/45 D 17 05W	RSC		8J x 17 EH2	43	-	122	
245/45 R 17 95W	KSC	-	8J x 17 EH2+	43 43 43	-	122,277,278	
245/40 R 18 93W	RSC		8J x 18 EH2	43	-	123,124,135M,152i	
	RSC	-	8J x 18 EH2+	43	-	124,135M,152i,246	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	43	-	124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	55	-	124	
Winter (M+S):							
225/50 P 17 04H	Gr 1/DGC		7½J x 17 EH2	43	13 -	138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243	
245/45 R 17 99 V XL	DCC		8J x 17 EH2	43	-	122	
243/43 K 1 / 99 V AL	RSC	-	8J x 17 EH2+	43	-	122,277,278	
245/40 R 18 97 V XL	RSC		8J x 18 EH2	43	-	123,124,135M,152i	
243/40 K 10 9/ V AL	KSC	-	8J x 18 EH2+	43	-	124,135M,152i,246	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Allrad Limousine

Stand 04/08

530xd/xdA (M57D3	530xd/xdA (M57D30)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.					
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM				
Sommer:										
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2	43	-	138				
223/30 K 1 / 94 W	Stu/KSC	-	7½J x 17 EH2+	43	-	138,243				
245/45 R 17 95W	RSC		8J x 17 EH2	43	-	122				
245/45 K 1 / 95 W	RSC	_	8J x 17 EH2+	43	-	122,277,278				
245/40 R 18 93Y	RSC		8J x 18 EH2	43	-	123,124,135M,152i				
243/40 K 10 93 I	RSC	-	8J x 18 EH2+	43	-	124,135M,152i,246				
18"-Mischbereifung: 1)										
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2/EH2+	43	-	124				
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2/EH2+	55	-	124				
Winter (M+S):										
225/50 R 17 94H	Std/RSC	_	7½J x 17 EH2	43	-	138				
223/30 K 1 / 94fi	Sid/KSC	-	7½J x 17 EH2+	43	-	138,243				
245/45 R 17 99 V XL	RSC		8J x 17 EH2	43	-	122				
243/43 K I / 99 V AL	KSC		8J x 17 EH2+	43	-	122,277,278				
245/40 R 18 97 V XL	RSC		8J x 18 EH2	43	-	123,124,135M,152i				
243/40 K 10 9/ V AL	NSC .	-	8J x 18 EH2+	43	-	124,135M,152i,246				
Reserverad:										
T 135/80 R 17 102M 1)	•	4.00B x 17 H2	-	18	12	-				

### Technisch mögliche Rad-/Reifenkombinationen MJ 2008 E60 M-Sportpaket

Standardantrieb	Standardantrieb									
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.						
	Rad (LM-Rad)	mm	St.	LM						
Sommer:										
Mischbereifung: 1)										
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M						
VA: 245/35 R 19 4)	8,5 x 19	18	-	172M						
HA: 275/30 R 19 4)	9,5J x 19	32	-	172M						
Winter (M+S):										
s.AG										

Allrad									
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.					
			St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M					
Winter (M+S):									
s.AG									

### Technisch mögliche Rad-/Reifenkombinationen MJ 2008 E60 BMW Individual

Standardantrieb	Standardantrieb									
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.						
	Rad (LM-Rad)	mm	St.	LM						
Sommer:										
Mischbereifung: 1)										
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i						
VA: 245/35 R 19 4)	8,5J x 19	18	-	228i						
HA: 275/30 R 19 4)	9,5J x 19	32	-	228i						
Winter (M+S):										
s.AG										

Allrad									
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.					
			St.	LM					
Sommer:									
Mischbereifung: 1)									
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i					
Winter (M+S):									
s.AG									

E60 M5 Limousine	E60 M5 Limousine									
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.						
	Rad (LM-Rad)	mm	St.	LM						
Sommer:										
Mischbereifung: 1) 2)										
VA: 255/40 ZR 19	8,5J x 19	12	-	166M						
HA: 285/35 ZR 19	9,5J x 19	28	-	166M						
VA: 255/40 ZR 19	8,5J x 19	12	-	167M						
HA: 285/35 ZR 19	9,5J x 19	28	-	167M						
Winter (M+S):										
VA: 245/45 R 18	8J x 18	14	-	184M						
HA: 245/45 R 18	8J x 18	14	-	184M						
Reserverad:										
3)	-	-	-	-						

E61 M5 Touring				
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.
	Rad (LM-Rad) mm S	St.	LM	
Sommer:				
Mischbereifung: 1) 2)				
VA: 255/40 ZR 19	8,5J x 19	12	-	166M
HA: 275/35 ZR 19	9J x 19	17	-	166M
VA: 255/40 ZR 19	8,5J x 19	12	-	167M
HA: 275/35 ZR 19	9J x 19	17	-	167M
Winter (M+S):				
VA: 245/45 R 18	8J x 18	14	-	184M
HA: 245/45 R 18	8J x 18	14	-	184M
Reserverad:				
3)	-	-	-	-

# Baureihe 5 (E60) - Limousine

			I	Т				
Reifendimension		Stahlscheiben- Rad (StRad)	Leichtmetall- Rad (LM-Rad)	IS mm	_	Styling Nr.		
	Tana (ou Tana)		St.	LM				
Sommer:								
225/55 R 16 95V	Std	-	7J x 16 H2	20	-	50,115,134,242		
			7½J x 17 EH2	20	-	116,138		
225/50 R 17 94W	Std/RSC		7½J x 17 EH2+	20	-	138,243,244		
223/30 K 1 / 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144		
			8J x 17 EH2+	20	-	122,245,277,278		
245/45 R 17 95W	RSC		8J x 17 EH2	20	-	122,144		
243/43 K 1 / 93 W	KSC	-	8J x 17 EH2+	20	-	122,245,277,278		
245/40 D 19 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
18"-Mischbereifung: 1)								
			8J x 18 EH2	20	_	32,89,124		
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	_	32,124,247		
			9J x 18 EH2	32	_	32,89,124		
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2+	32	-	32,124,247		
						- , , .		
400.25: 11 .:04)			1					
19"-Mischbereifung: 1)								
			8J x 19 EH2	20	-	101,125,128		
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M		
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269		
HA: 275/30 R 19 96Y XL	Std	_	9½J x 19 EH2	32	-	101,125,128,172M		
			9½J x 19 EH2+	32	-	128,172M,179,190,228i,269		
Winter (M+S):								
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242		
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242		
205/50 P 17.041	0.1/200		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244		
245/45 R 17 99 V XL	Bac		8J x 17 EH2	20	-	122,144		
	RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	†	18	12			

# Baureihe 5 (E60) - Limousine

525i/iA (N52B25OL) Reifendimension		Stahlscheiben-	Leichtmetall-	IS				
Kenenumension		Rad (StRad)	Rad (LM-Rad)	mm	St.			
Sommer:								
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134,242		
			7½J x 17 EH2	20	-	116,138		
			7½J x 17 EH2+	20	-	138,243,244		
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144		
			8J x 17 EH2+	20	-	122,245,277,278		
045/45 D 15 05W	pag		8J x 17 EH2	20	-	122,144		
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
18"-Mischbereifung: 1)								
VA: 245/40 R 18 93W	Pag	С -	8J x 18 EH2	20	-	32,89,124		
	RSC		8J x 18 EH2+	20	-	32,124,247		
HA : 275/25 D 10 05W	ngg		9J x 18 EH2	32	-	32,89,124		
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2+	32	-	32,124,247		
19"-Mischbereifung: 1)								
			8J x 19 EH2	20	-	101,125,128		
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M		
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269		
IIA : 275/20 D 10 06V VI	C+4		9½J x 19 EH2	32	-	101,125,128,172M		
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269		
Winter (M+S):								
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242		
225/50 D 17 0/H	Q+4/DQQ		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H	Std/RSC		7½J x 17 EH2+	20	-	138,243,244		
245/45 R 17 99 V XL	RSC		8J x 17 EH2	20	-	122,144		
273/43 K 1 / 77 V AL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

# Baureihe 5 (E60) - Limousine

530d/dA (M57D30),	530i/iA (	N52B30)				
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ing Nr.
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
			7½J x 17 EH2	20	-	116,138
225/50 R 17 94W	Std/RSC		7½J x 17 EH2+	20	-	138,243,244
223/30 K 1 / 94 W	Stu/KSC	-	8J x 17 EH2	20	-	122,144
			8J x 17 EH2+	20	-	122,245,277,278
245/45 R 17 95W	RSC		8J x 17 EH2	20	-	122,144
243/43 K 1 / 93 W	KSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93Y *)	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 18 93 1 · )	KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
18"-Mischbereifung: 1)						
	200	SC -	8J x 18 EH2	20	-	32,89,124
VA: 245/40 R 18 93Y *)	RSC		8J x 18 EH2+	20	-	32,124,247
HA 275/25 D 10 05W *\	DCC		9J x 18 EH2	32	-	32,89,124
HA: 275/35 R 18 95Y *)	RSC	-	9J x 18 EH2+	32	-	32,124,247
19"-Mischbereifung: 1)						
			8J x 19 EH2	20	-	101,125,128
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269
IIA. 275/20 D 10 0/W VI	Ctl		9½J x 19 EH2	32	-	101,125,128,172M
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269
Winter (M+S):						
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242
225/50 D 17 04H	C. 1/D.C.C		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
045/45 D 17 00 VVV	DCC		8J x 17 EH2	20	_	122,144
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	IS Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
005/50 D 45 0 434	0.1500		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
0.45/45 P. 45 05W	PGG		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 P 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
			8J x 18 EH2	20	-	32,89,124	
VA: 245/40 R 18 93W RS	RSC	:  -	8J x 18 EH2+	20	-	32,124,247	
***	naa		9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269	
			9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269	
Winter (M+S):							
205/50 P 45 04X	Gr 1/D.C.C.		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	<b>-</b>	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 99 V XL	RSC		8J x 17 EH2	20	·	122,144	
	KSC	-	8J x 17 EH2+	20	-	122,245,277,278	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	• 8		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
225/50 P 17 04W	Gr 1/D.C.C.		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 R 18 93Y	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
243/40 K 18 93 I	KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
			8J x 18 EH2	20	-	32,89,124	
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2+	20	-	32,124,247	
11. 055/25 D 10.051/	D.C.C.		9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269	
114 255/20 D 10 0/31 31	0.1		9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269	
Winter (M+S):							
005/50 D 45 0 :	0.1====		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244	
0.45/45 D 15 00 33 33	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
		Rad (StRad)	Rad (LM-Rad)	mm	_	LM		
Sommer:								
			7½J x 17 EH2	20	-	116,138		
225/50 P 15 0 4W	G: 1/D.G.G		7½J x 17 EH2+	20	-	138,243,244		
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144		
			8J x 17 EH2+	20	-	122,245,277,278		
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144		
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
245/40 R 18 93Y	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
243/40 K 10 93 I	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
18"-Mischbereifung: 1)				<u> </u>				
		2 -	8J x 18 EH2	20	-	32,89,124		
VA: 245/40 R 18 93Y	RSC		8J x 18 EH2+	20	-	32,124,247		
11. 075/25 D 10.051	pag		9J x 18 EH2	32	-	32,89,124		
HA: 275/35 R 18 95Y	RSC	RSC -	9J x 18 EH2+	32	-	32,124,247		
19"-Mischbereifung: 1)								
			8J x 19 EH2	20	-	101,125,128		
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M		
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269		
114 255/20 D 10 0/31 3/1	Q. 1		9½J x 19 EH2	32	-	101,125,128,172M		
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269		
Winter (M+S):								
005/50 P 45 0 :	0.1====		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244		
245/45 D 17 00 31 33	DCC		8J x 17 EH2	20	-	122,144		
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

# Baureihe 5 (E60) - Allrad Limousine

525i/iA (N53B30UL),	, JZSU/UA				,			
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:								
225/50 R 17 94W	Std/RSC		7½J x 17 EH2	43	-	138		
225/30 K 1 / 94W	Sia/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 D 17 05W	RSC		8J x 17 EH2	43	-	122		
245/45 R 17 95W	RSC	-	8J x 17 EH2+	43	-	122,277,278		
245/40 D 10 02W \$\	RSC		8J x 18 EH2	43	-	123,124,135M,152i		
245/40 R 18 93W *)	KSC	-	8J x 18 EH2+	43	-	124,135M,152i,246		
18"-Mischbereifung: 1) *)								
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2/EH2+	43	-	124		
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2/EH2+	55	-	124		
Winter (M+S):								
225/50 D 17 04H	G. 1/D.C.C		7½J x 17 EH2	43	-	138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 D 17 00 M WI	ngg		8J x 17 EH2	43	-	122		
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	43	-	122,277,278		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

# Baureihe 5 (E60) - Allrad Limousine

530d/dA (M57D30)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:									
225/50 P 17 04W	C41/DCC		7½J x 17 EH2	43	-	138			
225/50 R 17 94W	Std/RSC	-	7½J x 17 EH2+	43	-	138,243			
245/45 R 17 95W	RSC		8J x 17 EH2	43	-	122			
243/43 K 1 / 93 W	KSC	-	8J x 17 EH2+	43	-	122,277,278			
245/40 R 18 93Y	RSC		8J x 18 EH2	43	-	123,124,135M,152i			
243/40 K 18 93 i	KSC	-	8J x 18 EH2+	43	-	124,135M,152i,246			
18"-Mischbereifung: 1)									
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2/EH2+	43	-	124			
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2/EH2+	55	-	124			
Winter (M+S):									
225/50 D 17 04H	Gr 1/DGC		7½J x 17 EH2	43	-	138			
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243			
245/45 D 17 00 V VI	DCC		8J x 17 EH2	43	-	122			
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	43	-	122,277,278			
Reserverad:									
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-			

### Technisch mögliche Rad-/Reifenkombinationen MJ 2009 E60 M-Sportpaket

Standardantrieb								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M				
VA: 245/35 R 19 4)	8,5 x 19	18	-	172M				
HA: 275/30 R 19 4)	9,5J x 19	32	-	172M				
Winter (M+S):								
s.AG								

Allrad								
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.				
			St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M				
Winter (M+S):								
s.AG								

#### Technisch mögliche Rad-/Reifenkombinationen MJ 2009 E60 BMW Individual

Standardantrieb								
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i				
VA: 245/35 R 19 4)	8,5J x 19	18	-	228i				
HA: 275/30 R 19 4)	9,5J x 19	32	-	228i				
Winter (M+S):								
s.AG								

Allrad								
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.				
			St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i				
Winter (M+S):								
s.AG								

# Baureihe 5 (E61) - Touring

520d/dA (N47D20), 520i/	520d/dA (N47D20), 520i/iA (N43B20), 523i/iA (N52B25UL), 523i/iA (N53B25UL)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242			
		7½J x 17 EH2	20	-	116,138			
235/50 P 17 04W C/1/DCC		7½J x 17 EH2+	20	-	138,243,244			
225/50 R 17 94W Std/RSC	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144			
243/43 K 1 / 93 W KSC	-	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93W RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
243/40 K 18 93 W KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M			
1) KSC	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/55 R 16 95H Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242			
225/50 P 17 04H		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244			
245/45 D 17 00V VI 2) BCC		8J x 17 EH2	20	-	122,144			
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

525d/dA (M57D30UL)	525d/dA (M57D30UL)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
225/55 R 16 95W Sto	1 -	7J x 16 H2	20	-	50,115,134,242			
		7½J x 17 EH2	20	-	116,138			
225/50 P 17 04W C(1/PG)	,	7½J x 17 EH2+	20	-	138,243,244			
225/50 R 17 94W Std/RSG	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95W RSC	,	8J x 17 EH2	20	-	122,144			
243/43 K 1 / 93 W KSC	,   <del>-</del>	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93W RSC	,	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
243/40 K 18 93 W KSC	,   <del>-</del>	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 93Y XL RSC	,	8½J x 19 EH2	18	-	125,128,172M			
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/55 R 16 95H Std	1 -	7J x 16 H2	20	-	50,115,134,242			
225/50 P 17 04H		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94H Std/RSC	;	7½J x 17 EH2+	20	-	138,243,244			
245/45 D 17 00V VI 2) BCC		8J x 17 EH2	20	-	122,144			
245/45 R 17 99V XL 2) RSC	,   <del>-</del>	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

525i/iA (N52B25OL),	525i/iA (N52B25OL), 525i/iA (N53B30UL)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242			
		7½J x 17 EH2	20	-	116,138			
225/50 D 17 04V C44/DCC		7½J x 17 EH2+	20	-	138,243,244			
225/50 R 17 94Y Std/RSC	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 D 17 05W DCC		8J x 17 EH2	20	-	122,144			
245/45 R 17 95W RSC	-	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
243/40 K 18 93 I KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 RSC		8½J x 19 EH2	18	-	125,128,172M			
93Y XL 1) RSC	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242			
225/50 R 17		7½J x 17 EH2	20	-	116,138			
94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244			
245/45 R 17 99V		8J x 17 EH2	20	-	122,144			
XL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

530d/dA (M57D30)	530d/dA (M57D30)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
		7½J x 17 EH2	20	-	116,138			
225/50 D 17 04V - C41/DCC		7½J x 17 EH2+	20	-	138,243,244			
225/50 R 17 94Y Std/RSC	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144			
245/45 R 17 95W RSC	-	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
243/40 K 18 93 i KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 RSC		8½J x 19 EH2	18	-	125,128,172M			
93Y XL 1) RSC	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242			
225/50 R 17		7½J x 17 EH2	20	-	116,138			
94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244			
245/45 R 17 99V RSC		8J x 17 EH2	20	-	122,144			
XL 2) RSC		8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

530i/iA (N52B30)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	v e			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:							
		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94Y Std/RS0		7½J x 17 EH2+	20	-	138,243,244		
225/50 K 1 / 94 Y Std/RS0	-	8J x 17 EH2	20	-	122,144		
		8J x 17 EH2+	20	-	122,245,277,278		
245/45 R 17 95Y RSG	,	8J x 17 EH2	20	-	122,144		
243/43 K 1 / 93 1 KSC	-	8J x 17 EH2+	20	-	122,245,277,278		
245/40 R 18 93Y RSG	,	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
243/40 K 16 93 1 KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
245/35 R 19 93Y XL RSG		8½J x 19 EH2	18	-	125,128,172M		
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269		
Winter (M+S):							
225/55 R 16 95H Std	d -	7J x 16 H2	20	-	50,115,134,242		
225/50 R 17 94H Std/RS0	,	7½J x 17 EH2	20	-	116,138		
223/30 K 1 / 94H Sta/KSC	-	7½J x 17 EH2+	20	-	138,243,244		
245/45 R 17 99V XL 2) RSG	1	8J x 17 EH2	20	-	122,144		
243/43 R 1 / 99 V AL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-		

# Baureihe 5 (E61) - Touring

530i/iA (N53B30OL)								
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
		7½J x 17 EH2	20	-	116,138			
225/50 B 17 04V C41/BC		7½J x 17 EH2+	20	-	138,243,244			
225/50 R 17 94Y Std/RS0	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95Y RSG	,	8J x 17 EH2	20	-	122,144			
243/43 K 1 / 93 1 KSC	-	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93Y RSC	7	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
243/40 K 18 93 1 KSV	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 93Y XL RSG	7	8½J x 19 EH2	18	-	125,128,172M			
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/50 P 17 04H		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94H Std/RS0	-	7½J x 17 EH2+	20	-	138,243,244			
045(45 D 45 00V VV 0) DGG		8J x 17 EH2	20	-	122,144			
245/45 R 17 99V XL 2) RSG	-	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

535dA (M57D30TOP)								
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94Y Std/RSC		7½J x 17 EH2+	20	-	138,243,244			
225/50 K 1 / 94 Y Std/RSC	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144			
243/43 K 1 / 93 1 KSC	-	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
245/40 K 10 75 1 KSC	_	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M			
1)		8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/50 D 17 04H		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244			
245/45 D 17 00V VI 2) P.C.C.		8J x 17 EH2	20	-	122,144			
245/45 R 17 99V XL 2) RSC	_	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

550i/iA (N62B48)								
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94Y Std/RSC		7½J x 17 EH2+	20	-	138,243,244			
225/50 K 1 / 94 Y Std/RSC	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144			
243/43 K 1 / 93 1 KSC	-	8J x 17 EH2+	20	-	122,245,277,278			
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
243/40 K 16 93 1 KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M			
1)		8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/50 R 17 94H Std/RSC		7½J x 17 EH2	20	-	116,138			
223/30 K 1 / 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244			
245/45 R 17 99V XL 2) RSC		8J x 17 EH2	20	-	122,144			
243/43 K 1 / 99 V AL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# **Baureihe 5 (E61) - Allrad Touring**

525i/iA (N53B30UL), 525d/dA (M57D30UL)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:									
225/50 R 17 94Y	Std/RSC		7½J x 17 EH2	43	-	138			
223/30 K 1 / 94 Y	Sid/KSC	-	7½J x 17 EH2+	43	-	138,243			
245/45 R 17 95W	RSC		8J x 17 EH2	43	-	122			
243/43 K 1 / 93 W	RSC	-	8J x 17 EH2+	43	-	122,277,278			
245/40 D 19 02W	RSC	-	8J x 18 EH2	43	-	123,124,135M,152i			
245/40 R 18 93Y			8J x 18 EH2+	43	-	124,135M,152i,246			
Winter (M+S):									
225/50 D 17 04H	Std/RSC		7½J x 17 EH2	43	-	138			
225/50 R 17 94H		-	7½J x 17 EH2+	43	-	138,243			
245/45 D 17 00V VI 2)	RSC		8J x 17 EH2	43	-	122			
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2+	43	-	122,277,278			
Reserverad:									
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-			

# **Baureihe 5 (E61) - Allrad Touring**

530i/iA (N52B30), 530i/iA (N53B30OL), 530d/dA (M57D30)									
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.				
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:									
225/50 R 17 94Y	Std/RSC		7½J x 17 EH2	43	-	138			
223/30 K 17 94 I	Std/RSC	-	7½J x 17 EH2+	43	-	138,243			
245/45 R 17 95Y	RSC		8J x 17 EH2	43	-	122			
243/43 K 17 93 I	KSC	=	8J x 17 EH2+	43	-	122,277,278			
245/40 P 10 03W	RSC -	-	8J x 18 EH2	43	-	123,124,135M,152i			
245/40 R 18 93Y			8J x 18 EH2+	43	-	123,124,135M,152i,246			
Winter (M+S):									
225/50 D 17 04H	G: 1/DGG		7½J x 17 EH2	43	-	138			
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243			
245/45 D 17 00V VI 2)	DSC		8J x 17 EH2	43	-	122			
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2+	43	-	122,277,278			
	_								
Reserverad:									
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-			

### Technisch mögliche Rad-/Reifenkombinationen MJ 2009 E61 M-Sportpaket

Standardantrieb	Standardantrieb							
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.				
			St.	LM				
Sommer:								
Mischbereifung: 1)								
VA + HA: 245/40 R 18 4)	8J x 18	20	-	135M				
Winter (M+S):								
s.AG								

Allrad							
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.			
	Rad (LM-Rad)	mm	St.	LM			
Sommer:							
Mischbereifung: 1)							
VA + HA: 245/40 R 18 4)	8J x 18	43	-	135M			
Winter (M+S):							
s.AG							

#### Technisch mögliche Rad-/Reifenkombinationen MJ 2009 E61 BMW Individual

Standardantrieb							
Reifendimension	Leichtmetall- Rad (LM-Rad)	IS mm	Stylin	ng Nr.			
			St.	LM			
Sommer:							
Mischbereifung: 1)							
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i			
Winter (M+S):							
s.AG							

Allrad							
Reifendimension	Leichtmetall-	IS	Stylii	ng Nr.			
	Rad (LM-Rad)	mm	St.	LM			
Sommer:							
Mischbereifung: 1)							
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i			
Winter (M+S):							
s.AG							

E60 M5 Limousine	E60 M5 Limousine							
Reifendimension	Tendimension Leichtmetall-Rad (LM-Rad) IS mm	IS	Stylin	ng Nr.				
		St.	LM					
Sommer:								
Mischbereifung: 1) 2)								
VA: 255/40 ZR 19	8,5J x 19	12	-	166M				
HA: 285/35 ZR 19	9,5J x 19	28	-	166M				
VA: 255/40 ZR 19	8,5J x 19	12	-	167M				
HA: 285/35 ZR 19	9,5J x 19	28	-	167M				
Winter (M+S):								
VA: 245/45 R 18	8J x 18	14	-	184M				
HA: 245/45 R 18	8J x 18	14	-	184M				
Reserverad:								
3)	-	-	-	-				

E61 M5 Touring	E61 M5 Touring							
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.				
	Rad (LM-Rad)	mm	St.	LM				
Sommer:								
Mischbereifung: 1) 2)								
VA: 255/40 ZR 19	8,5J x 19	12	-	166M				
HA: 275/35 ZR 19	9J x 19	17	-	166M				
VA: 255/40 ZR 19	8,5J x 19	12	-	167M	•			
HA: 275/35 ZR 19	9J x 19	17	-	167M	•			
Winter (M+S):								
VA: 245/45 R 18	8J x 18	14	-	184M				
HA: 245/45 R 18	8J x 18	14	-	184M				
Reserverad:								
3)	-	-	-	-				

# Baureihe 5 (E60) - Limousine

			I	Т	[a, u, v			
Reifendimension		Stahlscheiben- Rad (StRad)	Leichtmetall- Rad (LM-Rad)	IS mm	_	ing Nr.		
		Tuu (St. Tuu)	Tuu (EM Tuu)		St.	LM		
Sommer:								
225/55 R 16 95V	Std	-	7J x 16 H2	20	-	50,115,134,242		
			7½J x 17 EH2	20	-	116,138		
225/50 R 17 94W	Std/RSC		7½J x 17 EH2+	20	-	138,243,244		
223/30 K 1 / 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144		
			8J x 17 EH2+	20	-	122,245,277,278		
245/45 R 17 95W	RSC		8J x 17 EH2	20	-	122,144		
243/43 K 1 / 93 W	KSC	-	8J x 17 EH2+	20	-	122,245,277,278		
245/40 D 19 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
18"-Mischbereifung: 1)								
			8J x 18 EH2	20	_	32,89,124		
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	_	32,124,247		
	RSC -		9J x 18 EH2	32	_	32,89,124		
HA: 275/35 R 18 95W		-	9J x 18 EH2+	32	-	32,124,247		
						- , , .		
400.25: 11 .:04)			1					
19"-Mischbereifung: 1)								
			8J x 19 EH2	20	-	101,125,128		
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M		
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269		
HA: 275/30 R 19 96Y XL	Std	_	9½J x 19 EH2	32	-	101,125,128,172M		
			9½J x 19 EH2+	32	-	128,172M,179,190,228i,269		
Winter (M+S):								
205/60 R 16 92H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242		
225/55 R 16 95H	Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242		
205/50 P 17.041	0.1/200		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244		
045/45 D 17.00 V VV	Bac		8J x 17 EH2	20	-	122,144		
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	†	18	12			

# Baureihe 5 (E60) - Limousine

525i/iA (N52B25OL) Reifendimension		Stahlscheiben-	Leichtmetall-	IS		ing Nr.	
Kenenumension		Rad (StRad)	Rad (LM-Rad)	mm	St.		
Sommer:							
225/55 R 16 95W	Std	-	7J x 16 H2	20	-	50,115,134,242	
			7½J x 17 EH2	20	-	116,138	
			7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
045/45 D 15 05W	pag		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93W	Pag		8J x 18 EH2	20	-	32,89,124	
	RSC	-	8J x 18 EH2+	20	-	32,124,247	
HA : 275/25 D 10 05W	DCC		9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95W	RSC	-	9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269	
IIA : 275/20 D 10 06V VI	C+4		9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269	
Winter (M+S):							
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242	
225/50 D 17 0/H	Q+4/DQQ		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC		7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 99 V XL	RSC		8J x 17 EH2	20	-	122,144	
273/43 K 1 / 77 V AL	RSC		8J x 17 EH2+	20	-	122,245,277,278	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ling Nr.
		Rad (StRad)	Rad (LM-Rad)	mm		LM
Sommer:						
			7½J x 17 EH2	20	-	116,138
225/50 P 17 04W	C. 1/D.C.C.		7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144
			8J x 17 EH2+	20	-	122,245,277,278
245/45 D 17 05W	RSC		8J x 17 EH2	20	-	122,144
245/45 R 17 95W	KSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93Y *)	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 16 93 1 · )	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
18"-Mischbereifung: 1)				<u> </u>		
			8J x 18 EH2	20	_	32,89,124
	RSC	-	8J x 18 EH2+	20	-	32,124,247
			9J x 18 EH2	32	-	32,89,124
HA: 275/35 R 18 95Y *)	RSC	-	9J x 18 EH2+	32	-	32,124,247
19"-Mischbereifung: 1)						
			8J x 19 EH2	20	-	101,125,128
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269
HA: 275/30 R 19 96Y XL	Std		9½J x 19 EH2	32	-	101,125,128,172M
ПА. 2/3/30 К 19 90 1 AL	Siu	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269
Winter (M+S):						
225/55 R 16 95H	Std	-	7J x 16 H2	20	-	50,115,134,242
227/20 D 47 047	C44/DCC		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H	Std/RSC		7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 00 N N	RSC		8J x 17 EH2	20	-	122,144
245/45 R 17 99 V XL	KSC	-	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:				L		
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Stvl	ling Nr.	
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
205/50 5 45 0 433	0.1500		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
0.45/45 P. 45 05W	PGG		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i	
245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
			8J x 18 EH2	20	-	32,89,124	
VA: 245/40 R 18 93W	RSC	-	8J x 18 EH2+	20	-	32,124,247	
***	Dag	? -	9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95W	RSC		9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	-	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269	
			9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269	
Winter (M+S):							
225/50 P 17 04H	Gr 1/D.C.C.		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Std/RSC	<b>-</b>	7½J x 17 EH2+	20	-	138,243,244	
245/45 D 17 00 M M	RSC		8J x 17 EH2	20	·	122,144	
245/45 R 17 99 V XL	KSC	-	8J x 17 EH2+	20	-	122,245,277,278	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Limousine

Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ing Nr.
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:						
			7½J x 17 EH2	20	-	116,138
225/50 D 15 0 M	G: 1/DGG		7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144
			8J x 17 EH2+	20	-	122,245,277,278
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93Y	RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152
243/40 K 10 93 I	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
18"-Mischbereifung: 1)						
			8J x 18 EH2	20	-	32,89,124
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2+	20	-	32,124,247
			9J x 18 EH2	32	-	32,89,124
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2+	32	-	32,124,247
19"-Mischbereifung: 1)						
			8J x 19 EH2	20	-	101,125,128
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269
			9½J x 19 EH2	32	-	101,125,128,172M
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269
Winter (M+S):						
205/50 P 45 0 434	C+1/DCC		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 00 M M	RSC		8J x 17 EH2	20	·	122,144
245/45 R 17 99 V XL	KSC	-	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:						
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E60) - Limousine

550i/iA (N62B48) Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styl	ling Nr.	
		Rad (StRad)	Rad (LM-Rad)	mm	Styl	LM	
Sommer:							
			7½J x 17 EH2	20	-	116,138	
	0.1500		7½J x 17 EH2+	20	-	138,243,244	
225/50 R 17 94W	Std/RSC	-	8J x 17 EH2	20	-	122,144	
			8J x 17 EH2+	20	-	122,245,277,278	
245/45 D 17 05W	DCC		8J x 17 EH2	20	-	122,144	
245/45 R 17 95W	RSC	-	8J x 17 EH2+	20	-	122,245,277,278	
245/40 D 10 02W	DCC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152	
245/40 R 18 93Y	RSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247	
18"-Mischbereifung: 1)							
<u> </u>			8J x 18 EH2	20	-	32,89,124	
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2+	20	-	32,124,247	
	Dag		9J x 18 EH2	32	-	32,89,124	
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2+	32	-	32,124,247	
19"-Mischbereifung: 1)							
			8J x 19 EH2	20	_	101,125,128	
VA: 245/35 R 19 93Y XL	Std	-	8½J x 19 EH2	18	-	125,128,172M	
			8½J x 19 EH2+	18	-	128,172M,179,190,228i,269	
			9½J x 19 EH2	32	-	101,125,128,172M	
HA: 275/30 R 19 96Y XL	Std	-	9½J x 19 EH2+	32	-	128,172M,179,190,228i,269	
Winter (M+S):		_					
225/50 D 17 04H	Std/RSC		7½J x 17 EH2	20	-	116,138	
225/50 R 17 94H	Sta/KSC	-	7½J x 17 EH2+	20	-	138,243,244	
245/45 R 17 99 V XL	RSC		8J x 17 EH2	20	·	122,144	
∠¬J/¬J Κ 1 / JJ V ΛL	NSC	-	8J x 17 EH2+	20	-	122,245,277,278	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Allrad Limousine

525i/iA (N53B30UL), 525	d/dA (M57D30UL)	, 530i/iA (N52B30	)), 530	0i/iA	(N53B30OL)	
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:						
225/50 R 17 94W St	td/RSC -	7½J x 17 EH2	43	-	138	
225/30 K 1 / 94W S	id/RSC  -	7½J x 17 EH2+	43	-	138,243	
245/45 R 17 95W	RSC -	8J x 17 EH2	43	-	122	
245/45 K 1 / 95 W	KSC -	8J x 17 EH2+	43	-	122,277,278	
245/40 R 18 93W *)	RSC -	8J x 18 EH2	43	-	123,124,135M,152i	
245/40 K 18 93 W ")	KSC -	8J x 18 EH2+	43	-	124,135M,152i,246	
18"-Mischbereifung: 1) *)						
VA: 245/40 R 18 93W	RSC -	8J x 18 EH2/EH2+	43	-	124	
HA: 275/35 R 18 95W	RSC -	9J x 18 EH2/EH2+	55	-	124	
Winter (M+S):						
225/50 P 17 04H	1/pcc	7½J x 17 EH2	43	-	138	
225/50 R 17 94H St	td/RSC -	7½J x 17 EH2+	43	-	138,243	
245/45 D 17 00 V VI	DCC.	8J x 17 EH2	43	-	122	
245/45 R 17 99 V XL	RSC -	8J x 17 EH2+	43	-	122,277,278	
Reserverad:						
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E60) - Allrad Limousine

530d/dA (M57D30)							
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM	
Sommer:							
225/50 P 17 04W	Std/RSC	-	7½J x 17 EH2	43	-	138	
225/50 R 17 94W Std/RS0		-	7½J x 17 EH2+	43	-	138,243	
245/45 R 17 95W	RSC		8J x 17 EH2	43	-	122	
243/43 K 17 93 W	KSC	-	8J x 17 EH2+	43	-	122,277,278	
245/40 R 18 93Y	RSC	-	8J x 18 EH2	43	-	123,124,135M,152i	
	KSC	-	8J x 18 EH2+	43	-	124,135M,152i,246	
18"-Mischbereifung: 1)							
VA: 245/40 R 18 93Y	RSC	-	8J x 18 EH2/EH2+	43	-	124	
HA: 275/35 R 18 95Y	RSC	-	9J x 18 EH2/EH2+	55	-	124	
Winter (M+S):							
225/50 P 17 04H	G. 1/B.C.C		7½J x 17 EH2	43	-	138	
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243	
245/45 D 17 00 V VI	DCC		8J x 17 EH2	43	-	122	
245/45 R 17 99 V XL	RSC	-	8J x 17 EH2+	43	-	122,277,278	
Reserverad:							
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-	

# Baureihe 5 (E61) - Touring

520d/dA (N47D20), 520i/	iA (N43B20), 5	523i/iA (N52B2	25UL	ı), 52	23i/iA (N53B25UL)
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242
		7½J x 17 EH2	20	-	116,138
235/50 P 17 04W C/1/DCC		7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94W Std/RSC	-	8J x 17 EH2	20	-	122,144
		8J x 17 EH2+	20	-	122,245,277,278
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144
243/43 K 1 / 93 W KSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93W RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 18 93 W KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 93Y XL RSC		8½J x 19 EH2	18	-	125,128,172M
1) KSC	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269
Winter (M+S):					
225/55 R 16 95H Std	7J x 16 H2	7J x 16 H2	20	12	50,115,134,242
225/50 P 17 04H		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 00V VI 2) BCC		8J x 17 EH2	20	-	122,144
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

525d/dA (M57D30UL)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/55 R 16 95W Sto	1 -	7J x 16 H2	20	-	50,115,134,242
		7½J x 17 EH2	20	-	116,138
	,	7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94W Std/RSG	-	8J x 17 EH2	20	-	122,144
		8J x 17 EH2+	20	-	122,245,277,278
245/45 R 17 95W RSC	,	8J x 17 EH2	20	-	122,144
243/43 K 1 / 93 W KSC	,   <del>-</del>	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93W RSC	,	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
243/40 K 18 93 W KSC	,   <del>-</del>	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 93Y XL RSC	,	8½J x 19 EH2	18	-	125,128,172M
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269
Winter (M+S):					
225/55 R 16 95H Std	1 -	7J x 16 H2	20	-	50,115,134,242
225/50 P 17 04H		7½J x 17 EH2	20	-	116,138
225/50 R 17 94H Std/RSC	;	7½J x 17 EH2+	20	-	138,243,244
245/45 D 17 00V VI 2) BCC		8J x 17 EH2	20	-	122,144
245/45 R 17 99V XL 2) RSC	,   <del>-</del>	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

525i/iA (N52B25OL),	525i/iA (N53I	B30UL)			
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
225/55 R 16 95W Std	-	7J x 16 H2	20	-	50,115,134,242
		7½J x 17 EH2	20	-	116,138
225/50 D 17.0434 - C/1/DGC		7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94Y Std/RSC	-	8J x 17 EH2	20	-	122,144
		8J x 17 EH2+	20	-	122,245,277,278
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144
245/45 K 1 / 95 W KSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
245/40 K 18 93 Y KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 RSC		8½J x 19 EH2	18	-	125,128,172M
93Y XL 1) RSC	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269
Winter (M+S):					
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242
225/50 R 17		7½J x 17 EH2	20	-	116,138
94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 99V		8J x 17 EH2	20	-	122,144
XL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

530d/dA (M57D30)					
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM
Sommer:					
		7½J x 17 EH2	20	-	116,138
225/50 D 17 04V C44/DCC		7½J x 17 EH2+	20	-	138,243,244
225/50 R 17 94Y Std/RSC	-	8J x 17 EH2	20	-	122,144
		8J x 17 EH2+	20	-	122,245,277,278
245/45 R 17 95W RSC		8J x 17 EH2	20	-	122,144
245/45 R 17 95W RSC	-	8J x 17 EH2+	20	-	122,245,277,278
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i
245/40 K 18 93 Y KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247
245/35 R 19 RSC		8½J x 19 EH2	18	-	125,128,172M
93Y XL 1) RSC	=	8½J x 19 EH2+	18	-	172M,179,190,228i,269
Winter (M+S):					
225/55 R 16 95H Std	-	7J x 16 H2	20	-	50,115,134,242
225/50 R 17		7½J x 17 EH2	20	-	116,138
94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244
245/45 R 17 99V RSC		8J x 17 EH2	20	-	122,144
XL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278
Reserverad:					
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-

# Baureihe 5 (E61) - Touring

530i/iA (N52B30)	530i/iA (N52B30)								
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	Sty	ling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM				
Sommer:									
		7½J x 17 EH2	20	-	116,138				
225/50 R 17 94Y Std/RSC		7½J x 17 EH2+	20	-	138,243,244				
	-	8J x 17 EH2	20	-	122,144				
		8J x 17 EH2+	20	-	122,245,277,278				
245/45 R 17 95Y RSC	,	8J x 17 EH2	20	-	122,144				
243/43 K 1 / 93 1 KSC	-	8J x 17 EH2+	20	-	122,245,277,278				
245/40 R 18 93Y RSG	,	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i				
243/40 K 16 93 1 KSC	-	8J x 18 EH2+	20	-	32,124,135M,152i,246,247				
245/35 R 19 93Y XL RSG		8½J x 19 EH2	18	-	125,128,172M				
1)	-	8½J x 19 EH2+	18	-	172M,179,190,228i,269				
Winter (M+S):									
225/55 R 16 95H Std	d -	7J x 16 H2	20	-	50,115,134,242				
225/50 R 17 94H Std/RS0	,	7½J x 17 EH2	20	-	116,138				
223/30 K 1 / 94H Sta/KSC	-	7½J x 17 EH2+	20	-	138,243,244				
245/45 R 17 99V XL 2) RSG	1	8J x 17 EH2	20	-	122,144				
243/43 K 1 / 99 V AL 2) KSC	-	8J x 17 EH2+	20	-	122,245,277,278				
Reserverad:									
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-				

# Baureihe 5 (E61) - Touring

530i/iA (N53B30OL)								
Reifendimension	Stahlscheiben-		IS	Styling Nr.				
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM			
Sommer:								
		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94Y Std/RSC		7½J x 17 EH2+	20	-	138,243,244			
225/50 K 1 / 94 Y Std/RSC	-	8J x 17 EH2	20	-	122,144			
		8J x 17 EH2+	20	-	122,245,277,278			
245/45 R 17 95Y RSC		8J x 17 EH2	20	-	122,144			
243/43 K 17 93 1 KSC	-	8J x 17 EH2+	20	20 -	122,245,277,278			
245/40 R 18 93Y RSC	_	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i			
245/40 K 10 951 KSC	_	8J x 18 EH2+	20	-	32,124,135M,152i,246,247			
245/35 R 19 93Y XL RSC	_	8½J x 19 EH2	18	-	125,128,172M			
1)		8½J x 19 EH2+	18	-	172M,179,190,228i,269			
Winter (M+S):								
225/50 R 17 94H Std/RSC		7½J x 17 EH2	20	-	116,138			
225/50 R 17 94H Std/RSC	-	7½J x 17 EH2+	20	-	138,243,244			
245/45 D 17 00V VI 2) DCC		8J x 17 EH2	20	-	122,144			
245/45 R 17 99V XL 2) RSC	-	8J x 17 EH2+	20	-	122,245,277,278			
Reserverad:								
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-			

# Baureihe 5 (E61) - Touring

535dA (M57D30TOP)							
Reifendimension	Stahlscheiben-	Leichtmetall-	IS	, 0			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:							
		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94Y Std/RS0	,	7½J x 17 EH2+	20	-	138,243,244		
223/30 K 1 / 941 Std/KSC	,   <del>-</del>	8J x 17 EH2	20	-	122,144		
		8J x 17 EH2+	20	-	122,245,277,278		
245/45 R 17 95Y RSC	1	8J x 17 EH2	20	-	122,144		
243/43 K 17 93 1 K3C	-	8J x 17 EH2+	20	-	122,245,277,278		
245/40 R 18 93Y RSC		8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
2+3/+0 K 10 /31 K5C	, -	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
245/35 R 19 93Y XL RSC	,   _	8½J x 19 EH2	18	-	125,128,172M		
1)	, and the second	8½J x 19 EH2+	18	-	172M,179,190,228i,269		
Winter (M+S):							
225/50 P 17 04H	,	7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H Std/RSC	;	7½J x 17 EH2+	20	-	138,243,244		
245/45 D 17 00V VI 2) DCC		8J x 17 EH2	20	-	122,144		
245/45 R 17 99V XL 2) RSC	, <u> </u>	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-,	18	12	-		

# Baureihe 5 (E61) - Touring

550i/iA (N62B48)							
Reifendimension	Stahlscheiben-		IS	Styling Nr.			
	Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:							
		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94Y Std/RS		7½J x 17 EH2+	20	-	138,243,244		
225/50 R 17 94Y Std/RS	~ <b>   -</b>	8J x 17 EH2	20	-	122,144		
		8J x 17 EH2+	20	-	122,245,277,278		
245/45 R 17 95Y RS	7	8J x 17 EH2	20	-	122,144		
243/43 K 1 / 93 1 KS	<u> </u>	8J x 17 EH2+	20	-	122,245,277,278		
245/40 R 18 93Y RS	7	8J x 18 EH2	20	-	32,71,89,123,124,129,135M,152i		
243/40 K 18 93 1 KS	_    -	8J x 18 EH2+	20	-	32,124,135M,152i,246,247		
245/35 R 19 93Y XL RS	7	8½J x 19 EH2	18	-	125,128,172M		
1)	_   -	8½J x 19 EH2+	18	-	172M,179,190,228i,269		
Winter (M+S):							
225/50 D 17 04H		7½J x 17 EH2	20	-	116,138		
225/50 R 17 94H Std/RS	J   -	7½J x 17 EH2+	20	-	138,243,244		
245/45 D 17 00V VI 2) DC		8J x 17 EH2	20	-	122,144		
245/45 R 17 99V XL 2) RS	~ <b>   -</b>	8J x 17 EH2+	20	-	122,245,277,278		
Reserverad:							
T 135/80 R 17 102M 1)	4.00B x 17 H2	-	18	12	-		

# **Baureihe 5 (E61) - Allrad Touring**

525i/iA (N53B30UL), 525d/dA (M57D30UL)								
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Styling Nr.			
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:								
225/50 R 17 94Y	Std/RSC		7½J x 17 EH2	43	-	138		
225/30 K 1 / 94 Y	Sta/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 D 17 05W	DSC		8J x 17 EH2	43	-	122		
245/45 R 17 95W	RSC	-	8J x 17 EH2+	43	-	122,277,278		
245/40 D 10 02W	RSC -	-	8J x 18 EH2	43	-	123,124,135M,152i		
245/40 R 18 93Y			8J x 18 EH2+	43	-	124,135M,152i,246		
Winter (M+S):								
225/50 D 17 04H	G. 1/D.C.C.		7½J x 17 EH2	43	-	138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 D 17 00V VI 2)	Pag		8J x 17 EH2	43	-	122		
245/45 R 17 99V XL 2)	RSC	-	8J x 17 EH2+	43	-	122,277,278		
	_							
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

# **Baureihe 5 (E61) - Allrad Touring**

530i/iA (N52B30), 530i/iA (N53B30OL), 530d/dA (M57D30)								
Reifendimension		Stahlscheiben-	Leichtmetall-	IS	Sty	Styling Nr.		
		Rad (StRad)	Rad (LM-Rad)	mm	St.	LM		
Sommer:								
225/50 R 17 94Y	Std/RSC		7½J x 17 EH2	43	-	138		
223/30 K 17 94 I	Std/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 R 17 95Y	RSC		8J x 17 EH2	43	-	122		
243/43 K 17 93 I	KSC	=	8J x 17 EH2+	43	-	122,277,278		
245/40 R 18 93Y	RSC -		8J x 18 EH2	43	-	123,124,135M,152i		
243/40 K 18 93 I		-	8J x 18 EH2+	43	-	123,124,135M,152i,246		
Winter (M+S):								
	G. 1/DGG		7½J x 17 EH2	43	-	138		
225/50 R 17 94H	Std/RSC	-	7½J x 17 EH2+	43	-	138,243		
245/45 D 17 00V VI 2)	RSC		8J x 17 EH2	43	-	122		
245/45 R 17 99V XL 2)		-	8J x 17 EH2+	43	-	122,277,278		
	_							
Reserverad:								
T 135/80 R 17 102M 1)		4.00B x 17 H2	-	18	12	-		

### Technisch mögliche Rad-/Reifenkombinationen MJ 2010 E61 Individual + M-Sportpaket

Standardantrieb						
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.		
	Rad (LM-Rad) mm	St.	LM			
Sommer:						
Mischbereifung: 1)						
VA + HA: 245/40 R 18 4)	8J x 18	20	-	152i, 135M		
Winter (M+S):						
s.AG						

Allrad						
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.		
	Rad (LM-Rad)	mm	St.	LM		
Sommer:						
Mischbereifung: 1)						
VA + HA: 245/40 R 18 4)	8J x 18	43	-	152i, 135M		
Winter (M+S):						
s.AG						

E61 M5 Touring					
Reifendimension	Leichtmetall-	IS	Stylin	ng Nr.	
	Rad (LM-Rad)	mm	St.	LM	
Sommer:					
Mischbereifung: 1) 2)					
VA: 255/40 ZR 19	8,5J x 19	12	-	166M	
HA: 275/35 ZR 19	9J x 19	17	-	166M	
VA: 255/40 ZR 19	8,5J x 19	12	-	167M	
HA: 275/35 ZR 19	9J x 19	17	-	167M	
Winter (M+S):					
VA: 245/45 R 18	8J x 18	14	-	184M	
HA: 245/45 R 18	8J x 18	14	-	184M	
Reserverad:					
3)	-	-	-	-	